

FEATURES AND SPECIFICATIONS



PowerCat 6 FTP Patch Cords PVC

Features and Benefits

Molex Premise Networks PowerCat 6 FTP patch cords are manufactured using high quality shielded four pair Category 6 stranded cable. Available in a range of colours and lengths, PowerCat 6 FTP patch cords are pre-terminated with RJ45 shielded plugs and feature cable strain relief boots with a plug latch protection cap.

Suitable for high speed data transmission, PowerCat 6 FTP patch cords have been designed to exceed the highest electrical performance standards in the industry and have been independently tested and verified by ETL SEMKO for Category 6 component compliance.

- Shielded 4 pair stranded cable
- Pre-terminated with WEBW shielded plugs
- Strain relief boots
- Independently tested

Compliant With

TIA/EIA-568-B.2-1, FCC Part 68 (Plug dimensions and tolerances), ISO 60603-7, ISO 11801:2002, EN 50173:2002

Approvals

UL
CSA
ETL Verified for Category 6 Component Compliance

Technical Information

Mechanical Characteristics - Cable

Conductor size: 26 AWG stranded bare copper
Screen Material: Aluminium/polyester shield with tinned copper drain wire
Max O.D.: 6.0mm
Jacket: PVC
Temperature range: -20°C to +60°C


Mechanical Characteristics - Plug

Operating life: Minimum 750 insertion cycles
Contact material: Copper alloy
Contact plating: 1.25 micrometres Au/Ni

Plug dimensions & tolerances compliant with FCC Part 68 and IEC 60603-7

Electrical Characteristics - Plug

Max voltage: 150 VAC (max)
Max current: 1.5A @ 25°C
Operating temperature: -40°C to 85°C



ORDERING INFORMATION

| Order No. | Description |
|--------------|---------------------------------|
| PCD-00304-0* | Patch Cord FTP 568A/B - 0.5m C6 |
| PCD-00305-0* | Patch Cord FTP 568A/B 1m C6 |
| PCD-00306-0* | Patch Cord FTP 568A/B 1.5m C6 |
| PCD-00307-0* | Patch Cord FTP 568A/B 2m C6 |
| PCD-00308-0* | Patch Cord FTP 568A/B 2.5m C6 |
| PCD-00309-0* | Patch Cord FTP 568A/B 3m C6 |
| PCD-00310-0* | Patch Cord FTP 568A/B 3.5m C6 |
| PCD-00311-0* | Patch Cord FTP 568A/B 4m C6 |
| PCD-00312-0* | Patch Cord FTP 568A/B 5m C6 |
| PCD-00313-0* | Patch Cord FTP 568A/B 6m C6 |
| PCD-00314-0* | Patch Cord FTP 568A/B 7m C6 |
| PCD-00315-0* | Patch Cord FTP 568A/B 8m C6 |
| PCD-00316-0* | Patch Cord FTP 568A/B 9m C6 |
| PCD-00317-0* | Patch Cord FTP 568A/B 10m C6 |

* Colour Options: C=Red, E=Grey, H=Blue, J=Green, K=Yellow



MOLEX PREMISE NETWORKS

Corporate Headquarters
Tel: 1-866-733-6659
www.molexpn.com

European Headquarters
Tel: 44 (0) 1489 527111
www.molexpn.co.uk

Pac Rim Headquarters
Tel: 61 3 9971 7111
www.molexpn.com.au



3 metre Category 6 FTP Patch Cord Typical (in - dB)

| NEXT | | | Return Loss | |
|-----------------|------------|------|-------------------|-------------|
| Frequency (MHz) | NEXT Limit | NEXT | Return Loss Limit | Return Loss |
| 1 | 65 | 93.0 | 19.9 | 43.1 |
| 4 | 65 | 83.9 | 21.6 | 35.1 |
| 8 | 65 | 79.3 | 22.5 | 28.2 |
| 10 | 65 | 78.4 | 22.8 | 26.9 |
| 16 | 61.5 | 78.8 | 23.4 | 26.5 |
| 20 | 59.6 | 75.7 | 23.7 | 28.9 |
| 25 | 57.7 | 70.8 | 24.0 | 39.1 |
| 31.25 | 55.7 | 66.4 | 23.0 | 31.0 |
| 62.5 | 49.9 | 66.3 | 20.0 | 26.3 |
| 100 | 46 | 59.0 | 18.0 | 26.6 |
| 200 | 40.3 | 56.1 | 14.9 | 33.2 |
| 250 | 38.5 | 44.2 | 14.0 | 22.1 |

MOLEX PREMISE NETWORKS

Corporate Headquarters
Tel: 1-866-733-6659
www.molexpn.com

European Headquarters
Tel: 44 (0) 1489 527111
www.molexpn.co.uk

Pac Rim Headquarters
Tel: 61 3 9971 7111
www.molexpn.com.au