



Service cordons
BP 30 Rue Velpeau
37110 CHATEAU-RENAULT

**FICHE TECHNIQUE
CORDON**
**TECHNICAL DATA SHEET
CABLE ASSEMBLY**

PART NUMBER : R285.212.000

Issue : 00


Date : 01/06/04

Customer : FARNELL UK

Specification : NA

Edition / Issue : - NA Date : NA

All dimensions are in mm



Connectors designation :

Connector 1 : **SMB straight plug crimp type
(R114.082.000)**
Torque Wrench : NA

Connector 2 : **SMB straight plug crimp type
(R114.082.000)**
Torque Wrench : NA

Cable designation :

KX3B (C291.150.010)

Cable colour :

Black

Outer diameter :

2.79mm

Marking:

NA

ELECTRICAL CHARACTERISTICS :

High Frequency

Characteristic impedance : **50Ω**

Frequency range : **DC-1GHz**

Insertion Loss : **NA**

Return Loss. : **NA**

Low Frequency

Insulation Resistance : **1000 Mohms mini**

Voltage Rating : **335 Vrms maxi**

CUSTOMER'S APPROVAL

Service or
Company's stamp

Name
Date

MECHANICAL CHARACTERISTICS :

Static bending radius : **10mm**

Cable crush resistance : **NA**

Life (connectors) : **500 matings**

ENVIRONMENTAL CHARACTERISTICS :

Temperature range : **-40°C/+85°C**

J.MOLLES	04/23	01/06/04	Création / First Issue	O. LE FOULER	1/1
Nom / Name	Edition / Issue	Date	Modification	Vérifié par / Checked by	