

## ELECTRONIC SERVICE—CASE **SECURITY** 6750

A case with the basic equipment of special tools for the installation and maintenance of

## complex protective devices and alarm systems



6750 (BERNSTEIN) SECURITY with tool set

6755 (BERNSTEIN) SECURITY without tool set

## Description:

Case made from deep-drawn, impact-resistant, grained black plastic, with sturdy aluminium frame, dustproof and rainproof, acid- and scratch-resistant. 64 tools are clearly arranged on two removable tool trays, one of it on both sides, and in the plastic tray with adjustable partitions in the bottom of the case. Further tools or accessories can be lodged in the tray until 60 mm height. The basic equipment for special operations at protective devices and alarm systems may efficiently be completed by special tools additionally recommended. The case has 2 locks.

Outside dimensions: 470 x 340 x 170 mm Weight without tools: ca. 4.600 kg Weight with tools: ca. 8.400 kg

## Tool set:

No.	Description of individual tools	No.	Description of individual tools
2-265	2 Test prods, red and black, extremely slim, pointed and flexible, blade made from 1 mm steel wire	6-600	Combination ring- and open-ended wrench, 7-piece set, CV, chrome-plated, 6,0, 7,0, 8,0, 9,0, 10,0, 11,0, 13,0 mm
2-701	Insertion tool with sensor for connecting the wires and simultaneously cutting of the	6-880	<b>Hexagon wrench keys</b> , 8-piece set in a wallet, 1/16", 5/64", 3/32", 1/8", 5/32", 3/16", 7/32", 1/4"
2-705	residual wire Contactless voltage detector VOLTtester	6-950	<b>Ballpoint wrench keys</b> , hexagon, 8-piece set in a wallet, 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0, 8.0 mm
3-112-2	<b>Side cutters</b> , 120 mm, for soft wire up to 1.0 mm Ø; with rounded head, without side face, double leaf spring, chrome-plated, with	6-995	TORX srewdrivers with bore-hole in the tip, 8-piece set in a box, T 9, T 10, T 15, T 20, T 25, T 27, T 30, T 40
3-0611	dip insulation  Crimping pliers, for BNC- and TNC-coaxial connectors	7-116 7-425	Engineer's hammer to DIN 1041, 300 g Dust brush
13-906 VDE	<b>VDE Side cutters</b> , 160 mm, for steel wire up to 1.6 mm Ø; chrome-plated, VDE safty insulation	7-506 7-535	Roller tape measure, 2 m Spirit level, 225 mm long
	<b>Telefone pliers</b> , 160 mm, chrome-plated, VDE safty insulation <b>Flat nose pliers</b> , 160 mm, with long jaws, chrome-plated,	7-616 8-375	Pocket hack saw PUK, with adjustable handle in a wallet ERSA gas soldering iron, Independent 75
13-936 VDE	VDE safty insulation Combination pliers, 160 mm, chrome-plated, VDE safty insulation	8-385 14-651 VDE 14-652 VDE	ERSA desoldering pump VAC X Screwdriver, with VDE insulation, blade 75 x 2.5 mm Screwdriver, with VDE insulation, blade 100 x 3.5 mm
4-431	Retaining srewdriver, for inserting and tightening slotted screws, blade made for CV. burnished, insulated, blade 100 x 3.0 mm	14-653 VDE 14-681 VDE	Screwdriver, with VDE insulation, blade 100 x 4.0 mm Cross-recess srewdriver, size 0, VDE, blade length 60 mm
4-437	<b>Retaining srewdriver</b> , for inserting and tightening cross-recess screws size 1, blade made for CV, burnished, insulated	14-682 VDE 14-683 VDE	Cross-recess srewdriver, size 1, VDE, blade length 80 mm Cross-recess srewdriver, size 2, VDE, blade length 100 mm
5-505 5-515	Insulation stripping tool, with hook blade, for cable Ø 8 - 28 mm Universal blade knife	14-684 VDE	Cross-recess srewdriver, size 3, VDE, blade length 150 mm
5-531	Automatic wire stripper Super, for all common stranded and solid conductors of 0.2 - 6.0 mm <sup>2</sup> , adjustable length stop of 5 - 12 mm, built-in side cutters for max. Ø 2 mm	2270	te the set we recommend: Service Set ACCENT, 9-piece set with ESD tools
5-535 6-103	Coax cable stripper for Coax cabel Ø 4.8 - 7.5 mm  Socket wrench, with special BERNSTEIN square handle, blade made from CV, chrome-plated, SW 4,5 mm	4-222 4-227 4-228	Srewdriver, blade 260 x 3.0 mm Cross-recess srewdriver, size 1, blade length 300 mm Cross-recess srewdriver, size 2, blade length 300 mm
6-104 6-105	Socket wrench, as above, AF 5.0 mm Socket wrench, as above, AF 5.5 mm	4-920	Interchangeable srewdriver set with ESD-handle, 9-piece, Slot 1.5/3.0 mm, 2.0/3.5 mm und 2.5/4.0 mm, KS Gr. 000/00, 0/1, TORX T 5/T 6, T 7L/T 8L, T 9L/T 10L, ("L" with bore hole)