

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

REVISIONS		DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
		796	A	RELEASED	HYO	10/9/01	JMM	3/27/02	DJC	3/27/02

Static dissipative dispensers come with a stainless steel pump with air tight check valve. Features an average surface resistivity of $10^9 \sim 10^{10}$ ohm, and can dissipate a $\pm 5000V$ charge in less than 2 seconds at 40% relative humidity.



DISCLAIMER:
ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.

DRAWN BY:	HISHAM ODISH	DATE:	10/9/01
CHECKED BY:	JEFF MCVICKER	DATE:	3/27/02
APPROVED BY:	DANIEL CAREY	DATE:	3/27/02



SPC TECHNOLOGY

DRAWING TITLE:			
6 OUNCE ESD SOLVENT DISPENSER, STANDARD PUMP			
SIZE	DWG. NO.	ELECTRONIC FILE	REV
A	1465	10N688.DWG	A
SCALE:	NTS	U.O.M.: INCHES [mm]	SHEET: 1 OF 1