# **Castors**



53 5101, 53 5102, 53 5103, 53 5111 and 53 5106



53 5902



53 5903 and 53 5911



53 7901, 53 7902, 53 7903



53 3101 and 53 3102



53 8221 and 53 8223



53 3103



http://www.farnell.com http://www.newark.com http://www.cpc.co.uk





53 3111



53 3106



#### Features:

- Black rubber tyre (85 shore A ±3) on a steel centre.
- Roller bearing bore.
- Standard duty loads.
- Zinc plated pressed steel castor housing.
- Suitable for use on compact floors eg cement, stone tiles, metallic, epoxy resins etc.
- Suitable for humid environments and outdoor use.
- Not recommended for use with organic solvents, chlorinated substances, hydrocarbons and mineral oils.
- Conductive wheel has an earthing resistance below 0.1m ohm in accordance with ISO 22878: 2004
- Temperature: -20°C to +60°C
- ISO2175.

### **Specification Table**

Description	Wheel Diameter	Tread/ Wheel Width	Overall Height	Plate Size	Hole Spacing	Hole Diameter	Offset	Carrying Capacity	Part Number
Standard Duty Swivel Castor, Rubber/Zinc	80	25	107	100 x 85	80 x 60	9	39	65	53 5101
	100	30	128				37	80	53 5102
	125	37.5	156				39	130	53 5103
	150	40	182				37	170	53 5111
	200	50	240	140 x 110	105 x 80	11	56	230	53 5106

Dimensions : Millimetres

### **Specification Table**

Description	Wheel Diameter	Tread/ Wheel Width	Overall Height	Plate Size	Hole Spacing	Hole Diameter	Carrying Capacity	Part Number
Standard Duty Fixed Castor, Rubber/Zinc	100	30	128	100 x 85 80	80 x 60	9	80	53 5902
	125	37.5	156				130	53 5903
	150	40	182				170	53 5911

Dimensions : Millimetres

http://www.farnell.com http://www.newark.com http://www.cpc.co.uk



## **Castors**



### **Specification Table**

Description	Wheel Diameter	Tread/Wheel Width	Overall Height	Offset	Plate Diameter	Hole Diameter	Carrying Capacity	Part Number
Standard Duty Bolt Hole Swivel Castor, Rubber/Zinc	73	25	107			39	65	53 7901
	100	30	128	12 80	37	80	53 7902	
	125	37.5	156			39	130	53 7903

Dimensions : Millimetres

### **Specification Table**

Description	Wheel Diameter	Tread/ Wheel Width	Overall Height	Offset	Plate Diameter	Hole Diameter	(E)	Carrying Capacity	Part Number
Standard Duty Swivel Castor with Foot Brake, Rubber/Zinc	73	25	107	12	80	39	120	65	53 8221
	125	37.5	156	12	80			130	53 8223

Dimensions : Millimetres

### **Specification Table**

Description	Wheel Diameter	Tread/ Wheel Width	Overall Height	Plate Size	Hole Spacing	Hole Diameter	Offset	## <u>[</u> (\$)_	Carrying Capacity	Part Number
Standard Duty Swivel Castor with Foot Brake, Rubber/Zinc	125	37.5	156	- 100 x 85	80 x 60	9	39	120	130	53 5423
Standard Duty Swivel Castor with Foot Brake, Top Plate	150	40	182		00 x 00	9	37	120	170	53 5431
Standard Duty Swivel Castor with Foot Brake, Rubber/Zinc	200	50	240	140 x 110	105 x 80	11	56	156	230	53 5426

Dimensions : Millimetres

### **Specification Table**

Description	Wheel Diameter	Tread/ Wheel Width	Hub Diameter	Hub Width	1 daN	Rolling Resistance	Carrying Capacity	Part Number
Roll Bearing Wheel, Rubber/Zinc	80	25	12	34	260	60	65	53 3101
Roll Bearing Wheel, Rubber Tyre/Zinc	100	30		34	300	75	80	53 3102
Roll Bearing Wheel, Rubber/Zinc	125	37.5	15	44	330	85	130	53 3103
Roll Bearing Wheel, Rubber Tyre/Zinc	150	40	15	44	350	100	170	53 3111
Roll Bearing Wheel, Only, Rubber/Zinc	200	50	20	58	410	140	230	53 3106

Dimensions: Millimetres

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability of oss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell plc 2009.

http://www.farnell.com http://www.newark.com http://www.cpc.co.uk

