

# Castor Nylon



### Features:

- This series offers injection virgin nylon 6 or polypropylene wheels which are available with plain bearing bore.

### The wheel can be fitted in the following castor housings:

- Medium duty top plate swivel, fixed and swivel with wheel brake.
- Medium duty bolt hole swivel and bolt hole swivel with wheel brake option.
- Medium duty threaded stem swivel and threaded stem swivel with wheel brake option.
- Medium duty triangular swivel top plate swivel castor.
- Natural colour nylon 6 and polypropylene wheels.

### Recommended Uses:

This wheel is recommended for standard to medium-heavy duty loads.


### Working Environment:

Manual handling applications.

Suitable for use compact floors e.g. cement, stone tiles, metallic, epoxy resins etc.

Particularly recommended for the food processing industry. Not recommended for use with concentrated organic acids or strong mineral acids.

Temperature : -30°C to +80°C for nylon 6 but capacity should be down rated below -10°C to +60°C  
0°C to +60°C for polypropylene wheels.



Dimensions : Millimetres

### Specification Table

Description	Wheel Diameter (D)	Thread Width (b)	Bore (d)	Hub Length (L)	Static Capacity (kg)	Carrying Capacity (kg)	Part Number
Castor, Spare, Nylon Wheel	63	25	11.2	33	125	100	68 0030

Dimensions : Millimetres

**Disclaimer** This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell plc 2009.

<http://www.farnell.com>  
<http://www.newark.com>  
<http://www.cpc.co.uk>

