



Features:

- Solder on a dispenser is 60/40 (22SWG).
- The dispensers delivers the solder in a much more manageable quantity, thus making it easier to use.
- The dispensers deliver the 60/40 in 6m length.

Handling and use Precautions:

Use these products in a well ventilated area. Fumes evolved during soldering should be extracted away from the operator.

Avoid inhaling fumes during soldering.

Wash hands thoroughly with soap and warm water after handling solder, particularly before eating and drinking or smoking.

Specifications

Solder Grade	Melting Temperature		Recommended Minimum Junction Temperature (°C)	Electrical Conductivity %IAC	Part Number
	Solids (°C)	Liquids (°C)			
60/40	183	188	248	11.5	SOLD0001

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. DURATOOL is the registered trademark of the Group. © Premier Farnell plc 2009.