



Lacquer Masking Tape

2060

FOD# 1517
page 1 of 3

Technical Data **September 1, 1998**

Supersedes July 1, 1995

Product Description A tape to mask lacquer paints from surfaces and to mask lacquered surfaces from other types of paints and lacquers.

Product Construction Backing: Crepe paper
Adhesive: Rubber
Color: Green
Standard Roll Length: 60 yds. (54.8m)

Typical Physical Properties **Note:** The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.

		<u>ASTM TEST METHOD</u>
Adhesion to Steel:	34 oz./in. width (37 N/100mm)	D-3330
Tensile Strength:	24 lbs./in. width (420 N/100mm)	D-3759
Elongation at Break:	8%	D-3759
Tape Thickness:	.0060 in. (0.15mm)	D-3652
Temperature Use Range:	Up to 200° F (93°C) for one hour	

- General Information**
1. Tape 2060 removes with little or no adhesive transfer to most surfaces for up to three days after application, even when subjected to sunlight exposure. Tape should be removed at a 90° angle.
 2. Tape 2060 remains supple and resists curl off when coated with paints and lacquers.
 3. Tape 2060 resists paint and lacquer flaking when the tape is removed from the job.
 4. Tape 2060 should not be subjected to prolonged outdoor exposure. Tape may become very difficult to remove.
 5. Tape 2060 is typically used at room temperature, but will function up to 200° F (93° C) for 1 hour.
 6. Tape 2060 is manufactured in an ISO 9002 registered plant to meet worldwide quality standards.

Shelf Life To obtain best performance, use this product within one year from date of manufacture and store under normal conditions of 70°F (21°C) and 50% R.H. in the original carton.

Features	<u>FEATURES</u>	<u>ADVANTAGES</u>	<u>BENEFITS</u>
	Rubber adhesive	Instant adhesion	Sticks easily/helps reduce labor
		Good holding power	Helps resist lifting or curling/helps reduce rework
	Crepe paper backing	Conformability	Easy handling/helps reduce time involved
		Easy tear	Good handling/helps reduce waste
	Seal/release treatment	Solvent and moisture	Helps resist curl off
		Controlled unwind	Easy to use/helps reduce waste
		Paint anchorage	Helps resist paint flaking
		Tape remains flexible	Helps resist slivering off the job

Technical Information and Data The technical information and data, recommendations, and other statements provided are based on tests or experience which 3M believes to be reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's method of application.

Warranty and Limited Remedy The 3M product will be free from defects in material and manufacture for a period of one (1) year from the date of manufacture. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of application. If the 3M product is defective within the warranty period stated above, your exclusive remedy and 3M's sole obligation shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product.

Limitation of Liability Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, warranty, negligence, or strict liability.

Scotch[®] Lacquer Masking Tape 2060

FOD#1517

page 3 of 3



Industrial Tape and Specialties Division

3M Center, Building 220-7W-03
St. Paul, MN 55144-1000
USA
1 800.722.5463
1 800.223.7427 Fax On Demand
www.3M.com

©3M 1999 70-0709-4448-6