



Repulpable Barricade Tapes 500 Series

Data Sheet

February 2009

Description Scotch® Repulpable Barricade Tapes 500 Series are nominal 10-mil tapes, constructed of a 100% cotton fabric. These reusable tapes are an excellent alternative to standard barricade tapes for areas where plastics are prohibited.

Agency Approvals & Self Certifications

RoHS 2002/95/EC



“RoHS Compliant 2002/95/EC” means that the product or part (“Product”) does not contain any of the substances in excess of the maximum concentration values in EU Directive 2002/95/EC, as amended by Commission Decision 2002/618/EC, unless the substance is in an application that is exempt under RoHS. This information represents 3M’s knowledge and belief, which may be based in whole or in part on information provided by third party suppliers to 3M.

Typical Properties

Not for specifications. Values are typical, not to be considered minimum or maximum. Properties measured at room temperature 73F (~23°C) unless otherwise stated.

Physical

| Property (Test Method) | Typical Value US units |
|------------------------|-----------------------------------|
| Color and Text | Variable (see availability chart) |
| Material | Cotton fabric |
| Thickness | 10-mil |
| Length | 150 ft. |
| Width | 3 in. |

Specifications

The tape shall be of good manufacturing quality in terms of appearance. It shall not gap or telescope more than 0.1 inches when stored at temperatures below 49°C. It must be flexible or not be stiff or brittle in applications ranging from below 0°C to about 38°C. The tape must be removable from the roll without difficulty.

The tape shall be smooth, uniform, and free of defects and irregularities. The print shall be uniform, the lettering free of lumps, free of visibly large voids and foreign materials. The warning words shall be legible, correctly spelled and fully printed. The ink shall be dry, firmly bonded to the substrate, and not transferable to non-printed parts of the film.

Shelf Life & Storage

This product has a 5-year shelf life from date of manufacture when stored in a humidity controlled storage (10°C/50°F to 27°C/80°F and <75% relative humidity).

Availability

Please contact your local distributor; available from 3M.com/electrical [Where to Buy] or call 1-800-245-3573.

| Product | Text | Color |
|------------|---------|--------|
| Scotch 515 | DANGER | Red |
| Scotch 516 | CAUTION | Yellow |

Scotch® Repulpable Barricade Tape 500 Series

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product, which are not contained in 3M's current publications, or any contrary statements contained on your purchase order, shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

**Warranty; Limited
Remedy; Limited
Liability**

This product will be free from defects in material and manufacture at the time of purchase. 3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

3M and Scotch are trademarks of 3M Company.

**Electrical Markets Division**

6801 River Place Boulevard
Austin, TX 78726-9000
800-245-3573 / 651-737-7222 (24 hours)
www.3m.com/electrical

Please recycle
© 3M 2009 All rights reserved
78-8127-8774-1 A