



PRODUCT INFORMATION

501-281

tesa 4263 / 4089

General Purpose Carton Sealing Tape

Product Description/ Application:

tesa 4263 is based on a PP backing with a rubber based adhesive and is available in two colours. Universally used to close cartons of light to medium weight range, tesa 4263 is able to be used in hand-held dispensers and automatic dispensing equipment.

Dimensions:

	- 1
II. Ctarteltame	<u> </u>
The second of th	-
86 660 ±000 m	
Lengths: 08 50 75 mm	
I Conguesta 75 mm	- 1
HERARITATION CONTRACTOR AND A CONTRACTOR	1
Transparent, Havana	. 4
II. Colour	and Section 1
	التناذينين

Other dimensions on enquiry

Technical Data: (mean values)

			THE PART OF THE PA
4.00		CONTRACTOR STATE OF THE PARTY O	
And the same of th	7 S. 18. 5 S. 18. (2) (42. 1) (4. 1)		11
	- * - * * * * * * * * * * * * * * * * *		Adhesive
	(1) 10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	TOMOSTION: I	Adnesive #
- 11 - 12 0.8 (20 m) (1 m) (1 8 22 2 1 m) (2 m)	tal: Tensile 📜	TOURS OF THE	* ************************************
Product Temperature Backing 10	idir vi Manana dak	office and the Total State State of the Control of	Strongth
- 1.0000((**※ ※ は100点(ない))を※	80.844 (2010	Satistreak i	Summun a
The C^{*} -	nece Strengto Li	CONTROL CONTROL	
利 - ASSESSON ASSESSION TO CONSTRUCT	11000	. 444 S C C C C C C C C C C C C C C C C C	11
1. 7.6.1.1.2.2.2.3.4.11.5.3.5.4.1.5.4.1		4	- 11
	>1° 4.		11 N/25 mm
- 11 - 12 - 12 - 12 - 12 - 12 - 12 - 12	μm 120 N/25 mm	120%	1 I NV / D MIN II
10090 PP 48	066 J. 1266 M/25 HJH F.	12,070 (1 1 11,22
8 4969 SBB MADDIEN SBC FF F 99	0111		11
4263 100°C PP 48	1.1		11
내 그 선생들은 그 전에 되는 그런 그 그 있었다. 그네는 그는 그를 다 보다 그를 다 되었다.		· 1	
41 contration and the contration will be a fail to the contration of			

4263,PI/B Issue No. 3 29.9/93

BDF ••••

Beiersdorf UK Ltd

Yeomans Drive, Blakelands, Milton Keynes MK14 5LS

Tel: 01908 211333 -Fax: 01908 211555

tase self-schesive tages are used successfully in many sectors to solve a variety of problems. Our publications contain numerous examples of such uses, intended to help towards a solution of your particular problems. Each tase product has been developed for a particular range of applications. Nevertheless, experience has shown that even for one and the same objective, the exact requirements may differ from case to case. We therefore, recommend that you garry out your own tests in each case, to confirm that the tase self-adhesive tase which you envisage using is appropriate for your periodular application. The advisory section of our Technical Service Department will be happy to assist. All information and recommendations are given by us in good faith, on the basis of practical experience, but without warranty