tesa	🦿 tesa worldwide Extranet login	Sitemap Search Contact www.tesa.com
INDUSTRIES OFFICE & AT HOME	ADHESIVE TAPE RANGE COMPANY HINTS & TIPS	
_ Automotive	< back to search results	PRODUCTS INDUSTRY
_ Automotive Refinishing	PRODUCT INFORMATION	Type in a search term or select a category
_ Corrugated Cardboard Industry	tesa® 4154	from the dropdow ns.
_ Craftsmen and Trades	Masking tape	4154
_ Electronics		All Assortments
_ Fairs & Exhibitions		All Applicationfields
_ Flexographic Printing		Reset Search
_ Furniture Industry		Reset Search
_ Marine Industry		
_ Paper & Print	٩.	Contact details:
Packaging & Logistics	Product Description	General: + 44 (0)1908 211333
_ Painting and Decorating	tesa® 4154 is a masking tape with a PVC-backing and acrylic adhesive. The product is	C/S Dept: + 44 (0)1908 500333
_ Trims & Profile Producers	designed to be used to mask glass and metal during etching.	∑ Contact us
_ Security, Brand Protection &	tesa® 4154 w ithstands diluted acids and alkalis. To achieve sharp definition of colour edges tesa® 4154 is also used for multi-colour painting purposes.	
Identification		Industries
_ Solar Industry	Main Applications	Adhesive Tape Guide Know your adhesive tapes, from Double Sided
_ Health Markets		Tape, Cloth Tape, Safety Tape, Masking Tape to
_ Product Range	Galvanising of metal Etching of glass and metal	Splicing Tape, Packaging Tape, Strapping Tape and more >>
_ tesanet Distributors	Masking during multi-colour painting	
	Technical Data Backing material PVC film Type of adhesive acrylic Total thickness 65 µm Adhesion to steel 3 N/cm Bongation at break 67 % Tensile strength 60 N/cm Properties Easy to remove yes Printability + Low unwinding force + Evaluation across relevant tesa assortment: ++ very good, + good, o medium, - low tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no waranties, expressed or implied, including, but not limited to any implied waranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you. back to top ↑	
	Print view Bookmark	
© tesa UK Ltd A tesa Company Imprint L	egal Terms Privacy Policy	