

**New 2010.**

Available now!

# Wiha Torque VDE interchangeable blades product amendment.

Protective insulation in the lower area completely integrated in the blade.



**287** Torque VDE Xeno interchangeable blade for terminal screws (slotted/ Phillips).  
Insulation up to 1000 V AC, GS-mark.  
For Wiha torque VDE screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish. Insulation moulded directly onto blade.  
Standards: Manufactured acc. to IEC 60900:2004, each tool individually tested at 10 000 Volts.  
Application: For electrical applications up to 1.000 V AC where recommended torque settings are important.

Order-No.	⊕	⦿	↔	↔	max. Nm	⊖
33571 7	PH2	3.8	220	65	5.5	1



**287** Torque VDE Phillips interchangeable blade.  
Insulation up to 1000 V AC, GS-mark.  
For Wiha torque VDE screwdrivers.

Blade: High quality chrome-vanadium-molybdenum steel, through hardened, black-finish. Insulation moulded directly onto blade.  
Standards: Tip DIN ISO 8764-1. Manufactured acc. to IEC 60900:2004, each tool individually tested at 10 000 Volts.  
Application: For electrical applications up to 1.000 V AC where recommended torque settings are important.

Order-No.	⊕	⦿	↔	↔	max. Nm	⊖
26693 6	PH2	3.8	220	65	5.5	1



**287** Torque VDE Xeno interchangeable blade for terminal screws (slotted/ Pozidriv).  
Insulation up to 1000 V AC, GS-mark.  
For Wiha torque VDE screwdrivers.

Order-No.	⊕	⦿	↔	↔	max. Nm	⊖
33586 1	PZ2	3.8	220	65	5.5	1



**287** Torque VDE Pozidriv interchangeable blade.  
Insulation up to 1000 V AC, GS-mark.  
For Wiha torque VDE screwdrivers.

Standards: Tip DIN ISO 8764-1.

Order-No.	⊕	⦿	↔	↔	max. Nm	⊖
26696 7	PZ2	3.8	220	65	5.5	1



Wiha Werkzeuge GmbH  
Obertalstraße 3-7  
D-78136 Schonach/Germany  
Tel. + 49 7722 959-0  
Fax. + 49 7722 959-159  
info@wiha.com  
www.wiha.com



### Wiha Torque VDE interchangeable blades.

- Protective insulation in the lower area completely integrated in the blade
- Constant, slim 65 mm diameter: low-lying, hard-to-reach fastening elements can be effortlessly reached
- One-off testing in a water bath according to IEC 60900:2004