











Angled Head Small

Length 115 mm

Model	L	A	B	C	D	Max. Cu	Weight	Description
572E  	115 mm	18 mm	10,5 mm	6,5 mm	6,5 mm	∅ 0,6 mm	68 g	✂ 40°, flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable Tip cutter. Medium size. Relieved jaws for easier access.
593AE  	115 mm	20 mm	10,5 mm	6,5 mm	4 mm	∅ 1,0 mm	68 g	✂ 50°, flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable Tip cutter. Cuts easily DIL leads from the rear. Cuts pins on dense PCB. Ideal maintenance tool.
582E  	115 mm	19 mm	10,5 mm	6,5 mm	7 mm	∅ 1,0 mm	68 g	✂ 45°, flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable Tip cutter medium size. A must when working on PCB's, cutting component leads. Also ideal for rework.
582EW  	115 mm	19 mm	10,5 mm	6,5 mm	7 mm	∅ 1,0 mm	70 g	✂ 45°, flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable, retention clip Same as 582E but with retention clip, holds wire scraps after cutting.

Length 120 mm

Model	L	A	B	C	D	Max. Cu	Weight	Description
555E  	120 mm	21 mm	10,5 mm	6 mm	6,5 mm	∅ 1,2 mm	68 g	✂ 40°, flush cut, high grade tool steel, anti-glare finish, ESD safe, resharpenable Tip cutter. Strong version.