TELEDATA ELECTRONIC SERVICE CASE

The case with a basic equipment of special tools for the installation and maintenance of complex telecommunication systems and data networks.

6700 (BERNSTEIN) TELEDATA with tool set 6715 (BERNSTEIN) TELEDATA without tool set

Description:

Case made from deep-drawn, impact-resistant, grained black plastic, with sturdy aluminium frame, dustproof and rainproof, acid- and scratch-resistant. 80 tools are clearly arranged on two removable tool trays, one of it on both sides, and in the plastic tray with adjustable partitions in the bottom of the case. The basic equipment for special operations at telecommunication systems and data networks may efficiently be completed by special tools additionally recommended.

The case has 2 locks.

Outside dimensions: 470 x 340 x 170 mm Weight without tools: approx. 4.600 kg Weight with tools: approx. 8.700 kg

Tool set

| No. | Description of individual tools | No. | Description of individual tools |
|-----------|---|----------------|---|
| 2-265 | 2 test prods, red and black, extremely slim, pointed and flexible, blade made | 6-103 | Socket wrench 4.5 mm, chrome vanadium, chrome-plated, with square handle |
| | from 1 mm steel wire | 6-104 | Socket wrench |
| 2-601 | IC-tweezers, nickel-plated, 125 mm, for gripping, inserting and removing IC's | 6-105 | 5.0 mm, chrome vanadium, chrome-plated, with square handle Socket wrench |
| 2-620 | PLCC-extractor | | 5.5 mm, chrome-vanadium, chrome-plated, with square handle |
| 2-701 | Insertion tool with sensor for connecting the wires and simultaneously cutting off the residual wire | 6-500-12 | Double open-ended wrench, 12 x 13 mm, chrome vanadium, chrome-plated |
| 3-112-2 | Side cutters, | 6-500-18 | Double open-ended wrench, |
| | 120 mm, for soft wire up to 1.0 mm, with rounded head, double leaf spring, chrome-plated, with red insulation | 6-600 | 18 x 19 mm, chrome vanadium, chrome-plated Combination ring- and open-ended wrench, |
| 3-134 VDE | Side cutters, | 6-600 | 7-piece set, chrome vanadium, chrome-plated, 6.0, 7.0, 8.0, 9.0, |
| | 160 mm, for steel wire up to 1.6 mm Ø, chrome-plated, with VDE | 0.000.10 | 10.0, 11.0, 13.0 mm Combination ring- and open-ended wrench. |
| 3-235-1 | safety insulation Telephon pliers, | 6-600-12 | 12 mm, chrome vanadium, chrome-plated |
| | 145 mm, chrome-plated, with BERNSTEINIT-insulation | 6-600-17 | Combination ring- and open-ended wrench, |
| 3-532-1 | Flat nose pliers, 160 mm, with long jaws, chrome-plated, with BERNSTEINIT-insulation | 6-600-19 | 17 mm, chrome vanadium, chrome-plated Combination ring- and open-ended wrench, |
| 3-585-1 | Quick-action water pump pliers, | | 19 mm, chrome vanadium, chrome-plated |
| | 175 mm, made from chrome vanadium, chrome-plated, with BERNSTEINIT-insulation | 6-880 | Hexagon wrench keys, 8-piece set, in a wallet, 1/16", 5/64", 3/32", 1/8", 5/32", 3/16", 7/32", 1/4" |
| 3-732-1 | Combination pliers, | 6-950 | Ballpoint wrench keys, hexagon, |
| 0.0005 | 160 mm, chrome-plated, with BERNSTEINIT-insulation | 0.005 | 8-piece set, in a wallet, 1.5, 2.0, 2.5, 3.0, 4.0, 5.0, 6.0, 8.0 mm Torx screwdrivers with bore-hole in the tip. |
| 3-0605 | Combination crimping pliers, 200 mm, for connector types 6P/6C, 6P/4C, 6P/2C, 8P/8C | 6-995 | 8-piece set, in a box, T 9, T 10, T 15, T 20, T 25, T 27, T 30, T 40 |
| 4-222 | Screwdriver | 7-425 7-506 | Duster |
| | with special square BERNSTEIN handle, blade made from chrome vanadium, chrome-plated, 260 x 3.0 mm, with black tip | 7-506 7-616 | Roller tape measure, 2 m Pocket saw. |
| 4-227 | Crosspoint-screwdriver, size 1, | | with adjustable wooden handle, in a wallet |
| | with special square BERNSTEIN handle, blade made from chrome vanadium, chrome-plated, 300 mm, with black tip | 9-316/5 | 5 Chip-Container, conductive box with lid, black, internal dimensions: 118 x 32 x 14 mm |
| 4-228 | Crosspoint-screwdriver, size 2. | 14-601 VDE | Screwdriver |
| | with special square BERNSTEIN handle, blade made from chrome vanadium, chrome-plated, 300 mm, with black tip | 14 602 VDE | with VDE-insulation, blade 75 x 2.5 mm Screwdriver |
| 4-431 | Retaining screwdrivers | | with VDE-insulation, blade 100 x 3.5 mm |
| | for inserting and tightening slotted screws, blade made from chrome vanadium, nickel-plated, insulated, 100 x 3.0 mm | 14-603 VDE | Screwdriver with VDE-insulation, blade 100 x 4.0 mm |
| 4-437 | Retaining screwdriver | 14-631 VDE | Cross-recess screwdriver, size 0. |
| | for inserting and tightening cross-recess screws size 1 | 44.000 VIDE | with VDE-insulation, blade length 60 mm |
| 5-107 | blade made from chrome vanadium, nickel-plated, insulated Engineer's tweezers. | 14-632 VDE | Cross-recess screwdriver, size 1, with VDE-insulation, blade length 80 mm |
| | made from steel, with bent tips, 150 mm, nickel-plated | 14-633 VDE | Cross-recess screwdriver, size 2, |
| 5-117 | Engineer's tweezers, made from steel, straight-flat-wide, 145 mm, nickel-plated | 14-634 VDE | with VDE-insulation, blade length 100 mm Cross-recess screwdriver, size 3. |
| 5-240 | Warding files, | 554 102 | with VDE-insulation, blade length 150 mm |
| 5-505 | 6-piece set, with wooden handles, in plastic wallet Insulation stripping tool | | |
| 0-000 | for cable diameter of 8 up to 28 mm | | |

TELEDATA 6700 ELECTRONIC SERVICE CASE

The service case for the ambitious Telecommunication engineer



