

Position Sensor Rectilinear



Features:

- Contactless linear sensor.
- IP64 debris proof, splash proof.
- Ideal for hydraulic and pneumatic position sensing.
- Liquid level capability.
- Upon request.
- Male or female nicomatic connectors.
- Corresponding exterior magnet.

Specifications:

Mechanical:

Life cycle : >1 million.
Height : ≤3.50mm (0.138 inches).
Actuation force : 0.09 to 0.11 lbs pull force at desired distance (pull force rating is for the exterior magnet using a test plate of cold rolled steel).

Environmental:

Operating temperature : up to +85°C.
IP rating of active area : IP64.

Electrical:

Resistance-standard : 10kΩ (lengths >300mm = 20kΩ).
Resistance-custom : 5k to 500kΩ.
Resistance tolerance : ±20%.
Effective electrical travel : 8 to 1200mm.
Resolution : Depends on the exterior magnet strength and distance to the magnetopot.
Power rating : 0.50 Watt continuous, 1 watt peak.
Dielectric value : No affect at 500V ac for 1 minute.
Independent linearity : ±5% (±1% available).
Hysteresis : 3mm*.

Note : * The hysteresis is directly affected by the drive magnet size, strength, and distance from the internal magnet.
* Requires magnet


<http://www.farnell.com>
<http://www.newark.com>
<http://www.cpc.co.uk>



Position Sensor Rectilinear




Stock Linear MagnetoPots




A	12.50 (0.492)	25.00 (0.984)	50.00 (1.969)	100.00 (3.937)	150.00 (5.906)	171.189 (6.768)	200.00 (7.874)	300.00 (11.811)	400.00 (15.748)	500.00 (19.685)	750.00 (29.528)	1000.00 (39.370)
P	28.36 (1.117)	40.86 (1.609)	65.86 (2.593)	115.86 (4.562)	165.86 (6.531)	185.86 (7.318)	215.86 (8.499)	315.86 (12.436)	415.86 (16.373)	515.86 (20.310)	765.86 (30.153)	1015.86 (39.995)
T	12.70 (0.500)		24.89 (0.980)									

Dimensions : Millimetres (Inches)

Electrical Schematic




Material Cross-Section




Position Sensor Rectilinear



Standard Connector Options



Crimpflex Solder Tab (ST)




Crimpflex Short Male Pins (MP)



Crimpflex Female Receptacles with a Plain Housing (RH)




Crimpflex Female Receptacles with a Latch Housing (RL)



Crimpflex Female Receptacles with a Detent Housing (RD)

Stock Linear MagnetoPots



Dimensions : Millimetres (Inches)


<http://www.farnell.com>
<http://www.newark.com>
<http://www.cpc.co.uk>




Position Sensor Rectilinear



Electrical Schematic




Material Cross-Section



Part Number Table

Description	Part Number
Sensor, Linear, Magneto, 25mm	MP1-L-0025-103-5%-ST
Sensor, Linear, Magneto, 50mm	MP1-L-0050-103-5%-ST
Sensor, Linear, Magneto, 100mm	MP1-L-0100-103-5%-ST
Sensor, Linear, Magneto, 150mm	MP1-L-0150-103-5%-ST
Sensor, Linear, Magneto, 300mm	MP1-L-0300-103-5%-ST
Sensor, Linear, Magneto, 500mm	MP1-L-0500-103-5%-ST
Sensor, Linear, Magneto, Rotary	MP1-R-0046-353-103-5%-ST

Part Number Explanation:



- Series** : MP1 = MagnetoPot.
- Model** : L = Linear and R = Rotary.
- Active angle** : 0025 = 25, 0050 = 50, 0100 = 100, 0150 = 150, 0300 = 300 and 0500 = 500mm.
- Centre of active track** : 0046 = 45.57mm.
- Active angle** : 0353 = 353°.
- Resistance** : Active lengths ≤ 300 mm 103 = 10K Ω .
- Ind. linearity** : 5% = $\pm 5\%$.
- Connectors** : ST = Solder tab.

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC Multicomp is the registered trademark of the Group. © Premier Farnell plc 2010.