

List Price \$570.00 USD

Availability **Non-Stock Item: This item is not normally stocked in our distribution facility.****Technical Characteristics**

Ampere Rating	10A
Application	Conveyor systems, packaging, textiles, transfer machines, presses, woodworking equipment, paint lines and test laboratories
Contact Configuration	2 N.O./2 N.C.
Approvals	UL Listed File Number: E164353 CCN NKCR - CSA Certified File Number: LR44087 Class 321103 - CE Marked
Reset Operator	Pushbutton
Orientation	Cable on Left
Connection Type	(3) 0.5 Inch NPT
Contact Operation	Slow Make - Slow Break
Contact Rating	A300 - Q300
Maximum Voltage Rating	300V
Enclosure Type	Water tight and Dust tight (Indoor/Outdoor)
Features	Emergency Stop (latching)
Mounting Type	Surface
Pilot Light	Yes
Terminal Type	Screw Clamp
Type	XY2
Cable Length	165 Feet (max)
Enclosure Rating	NEMA 1/4/12

Shipping and Ordering

Category	22441 - Limit Switches, Cable Pull, Type XY2
Discount Schedule	T
GTIN	00785901196389
Package Quantity	1
Weight	3.73 lbs.
Availability Code	Non-Stock Item: This item is not normally stocked in our distribution facility.
Returnability	N
Country of Origin	FR

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.