

A	06/35/49	33P
B	01/87/56	33P
C	09/24/1	33P
D	01/89	33P

MICRO SWITCH FREEPORT, ILLINOIS, U.S.A. A DIVISION OF HONEYWELL FED. MFG. CODE 9189P	SWITCH-ENCLOSED	CATALOG LISTING 18CX SERIES CHART 1	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: center;">CONVERSION CHART</th> </tr> </thead> <tbody> <tr><td>7,25</td><td>.285</td></tr> <tr><td>7,92</td><td>.312</td></tr> <tr><td>8,5</td><td>.33</td></tr> <tr><td>9,4</td><td>.37</td></tr> <tr><td>18,3</td><td>.72</td></tr> <tr><td>20,3</td><td>.80</td></tr> <tr><td>22,3±1,5</td><td>.880±.059</td></tr> <tr><td>25,4</td><td>1.00</td></tr> <tr><td>32,0</td><td>1.26</td></tr> <tr><td>40,0</td><td>1.57</td></tr> <tr><td>50,8</td><td>2.00</td></tr> <tr><td>80,0</td><td>3.15</td></tr> <tr><td>96,0</td><td>3.78</td></tr> <tr><td>98,0</td><td>3.86</td></tr> <tr><td>101,6</td><td>4.00</td></tr> <tr><td>104,0</td><td>4.09</td></tr> <tr><td>1,25 Nm</td><td>.922 PF</td></tr> </tbody> </table>	CONVERSION CHART		7,25	.285	7,92	.312	8,5	.33	9,4	.37	18,3	.72	20,3	.80	22,3±1,5	.880±.059	25,4	1.00	32,0	1.26	40,0	1.57	50,8	2.00	80,0	3.15	96,0	3.78	98,0	3.86	101,6	4.00	104,0	4.09	1,25 Nm	.922 PF
CONVERSION CHART																																							
7,25	.285																																						
7,92	.312																																						
8,5	.33																																						
9,4	.37																																						
18,3	.72																																						
20,3	.80																																						
22,3±1,5	.880±.059																																						
25,4	1.00																																						
32,0	1.26																																						
40,0	1.57																																						
50,8	2.00																																						
80,0	3.15																																						
96,0	3.78																																						
98,0	3.86																																						
101,6	4.00																																						
104,0	4.09																																						
1,25 Nm	.922 PF																																						
<p>NOTES</p> <p>1 - EXPLOSION PROOF-UNDERWRITERS LAB INC LISTING FOR HAZARDOUS LOCATIONS CLASS I, GROUPS B, C AND D; CLASS II, GROUPS E, F AND G</p> <p>2 - ALUMINUM ENCLOSURE FINISHED WITH BLUE AND BLACK EPOXY PAINT</p> <p>3 - 4-20 ma ANALOG OUTPUT, ADJUSTABLE CW OR CCW FOR 15° TO 90° SPANS</p> <p>4 - FOR USE IN TEMPERATURES UP TO 85°C</p> <p>5 - SEE (M) 7CX CHARTS 1 & 2 FOR LEVER ACTUATORS</p> <p>6 - UNIT PROVIDES NO SHAFT RESTORING FORCE, THE ACTUATING DEVICE MUST CONTROL MOVEMENT OF SHAFT</p>																																							
<p>THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.</p> <p style="text-align: center;">THIRD ANGLE PROJECTION</p> <p style="text-align: center;">SCALE 3/4 TO 1</p> <p style="text-align: center;">DO NOT SCALE PRINT</p> <p style="text-align: center;">TOLERANCES</p> <p style="text-align: center;">APPLY TO DIMEN UNITS, CONVERSIONS AND ONLY FOR REFERENCE, UNLESS NOTED, TOLERANCES ARE:</p> <table border="1" style="width: 100%; border-collapse: collapse; font-size: small;"> <tr> <th>DIM.</th> <th>TOL.</th> <th>DIM.</th> <th>TOL.</th> </tr> <tr> <td>DR PLACES</td> <td>± .004</td> <td>DR PLACES</td> <td>± .004</td> </tr> <tr> <td>DR PLACES</td> <td>± .002</td> <td>DR PLACES</td> <td>± .002</td> </tr> <tr> <td>DR PLACES</td> <td>± .001</td> <td>DR PLACES</td> <td>± .001</td> </tr> <tr> <td>DR PLACES</td> <td>± .0005</td> <td>DR PLACES</td> <td>± .0005</td> </tr> <tr> <td>DR PLACES</td> <td>± .0002</td> <td>DR PLACES</td> <td>± .0002</td> </tr> </table> <p style="text-align: center;">DESIGN LIMITS</p> <p style="text-align: center;">R&D MATERIAL-COMMERCIAL STANDARDS</p> <p style="text-align: center;">MICRO SWITCH STANDARDS APPLY</p> <p style="text-align: center;">DIMENSIONS ARE TO BE MET UNLESS PROTECTIVE COATINGS ARE APPLIED</p> <p style="text-align: center;">WEIGHT 1,13 Kg APPROX</p>			DIM.	TOL.	DIM.	TOL.	DR PLACES	± .004	DR PLACES	± .004	DR PLACES	± .002	DR PLACES	± .002	DR PLACES	± .001	DR PLACES	± .001	DR PLACES	± .0005	DR PLACES	± .0005	DR PLACES	± .0002	DR PLACES	± .0002													
DIM.	TOL.	DIM.	TOL.																																				
DR PLACES	± .004	DR PLACES	± .004																																				
DR PLACES	± .002	DR PLACES	± .002																																				
DR PLACES	± .001	DR PLACES	± .001																																				
DR PLACES	± .0005	DR PLACES	± .0005																																				
DR PLACES	± .0002	DR PLACES	± .0002																																				
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="2" style="text-align: center;">CHARACTERISTICS</th> </tr> </thead> <tbody> <tr> <td style="width: 50%;">OPERATING FORCE</td> <td style="width: 50%;">0,50 Nm MAX</td> </tr> <tr> <td>FULL OVERTRAVEL</td> <td>90° MAX</td> </tr> </tbody> </table>		CHARACTERISTICS		OPERATING FORCE	0,50 Nm MAX	FULL OVERTRAVEL	90° MAX	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">CAT. LIST</th> <th style="width: 55%;">DESCRIPTION</th> <th style="width: 20%;">ELECTRICAL DATA</th> </tr> </thead> <tbody> <tr> <td>18CX10</td> <td>ANALOG OUTPUT ONLY</td> <td>UL LISTED-FILE E 68247 ANALOG OUTPUT: 4-20 ma VOLTAGE RANGE: 12,5 TO 40VDC USE CLASS 2 POWER SUPPLY</td> </tr> <tr> <td>18CX0</td> <td>ANALOG OUTPUT ONLY</td> <td></td> </tr> </tbody> </table>		CAT. LIST	DESCRIPTION	ELECTRICAL DATA	18CX10	ANALOG OUTPUT ONLY	UL LISTED-FILE E 68247 ANALOG OUTPUT: 4-20 ma VOLTAGE RANGE: 12,5 TO 40VDC USE CLASS 2 POWER SUPPLY	18CX0	ANALOG OUTPUT ONLY																						
CHARACTERISTICS																																							
OPERATING FORCE	0,50 Nm MAX																																						
FULL OVERTRAVEL	90° MAX																																						
CAT. LIST	DESCRIPTION	ELECTRICAL DATA																																					
18CX10	ANALOG OUTPUT ONLY	UL LISTED-FILE E 68247 ANALOG OUTPUT: 4-20 ma VOLTAGE RANGE: 12,5 TO 40VDC USE CLASS 2 POWER SUPPLY																																					
18CX0	ANALOG OUTPUT ONLY																																						