MICRO SWITCH
FREEPORT ILLINOIS, U.S.A.
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

MINIATURE PRECISION LIMIT SWITCH

924CE2-S3



NOTES
1 - ZINC HOUSING FINISHED WITH GRAY PAINT
(2) THE MINIMUM PLUNGER TRAVEL PAST BREAK, FOR A SAFE CONTACT GAP IS .060
3 - SWITCH PROVIDES BREAK BEFORE MAKE CIRCUITRY



CIRCUIT DIAGRAM

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

CHARACTERISTICS	ELECTRICAL DATA	SCALE FULL
OPERATING FORCE - - - - - 5.1 LB MAX	CONTACT ARRANGEMENT S P D T D B	DO NOT SCALE PRINT
OVERTRAVEL - - - - - - - - - .039 MIN	10A - 250 VAC 1/3HP - 125 OR 250 VAC	TOLERANCES APPLY TO DESIGN UNITS. CONVERSIONS ARE ONLY FOR REFERENCE. UNLESS NOTED, TOLERANCES ARE ±

	DIM. mm	TOL. mm/in	DIM. in	TOL. mm/in
NO PLACES	X	1/.04		
ONE PLACE	X.X	0.4/.016	X.X	0.6/.03
TWO PLACES	X.XX	0.15/.006	X.XX	0.38/.01
THREE PLACES			X.XXX	0.13/.00
ANGLES				

DESIGN UNITS: SI METRIC ☐ US CUSTOMARY ■

WEIGHT

(2) THE MINIMUM PLUNGER TRAVEL PAST BREAK, FOR A SAFE CONTACT GAP IS .060
3 - SWITCH PROVIDES BREAK BEFORE MAKE CIRCUITRY
4 - SIDE EXIT CABLE



CIRCUIT DIAGRAM

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

THIRD ANGLE PROJECTION

CHARACTERISTICS	ELECTRICAL DATA	SCALE FULL
OPERATING FORCE - - - - - 5.1 LB MAX	CONTACT ARRANGEMENT S P D T D B	DO NOT SCALE PRINT
OVERTRAVEL - - - - - - - - - .039 MIN	10A - 250 VAC 1/3HP - 125 OR 250 VAC	UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

ONE PLACE	(.0)	± .030
TWO PLACE	(.00)	± .015
THREE PLACE	(.000)	± .005
ANGLES		±

924CE2-S3 M X2 ISSUE | DRAWING NUMBER | RELEASE NO. PR-14729 | REPLACES

REVISIONS
A C069061 L4F 15 AUG 91

FO-52848-A DRAWN TSK 16 OCT 86 CHECK | 23 NOV 88 CHECK | CHECK | CHECK | 31 AUG 89 CHECK

Downloaded from Elcodis.com electronic components distributor