



(M) EXA-AR
 ISSUE 2
 DRAWING NUMBER
 EXA-AR
 RELEASE NO.
 03DEC09
 REVISIONS
 B CD 14185
 4 DEC 58
 D CO1560M
 10 FEB 64
 D CO16851
 10 DEC 62
 E CO18276
 19 JUN 64
 F CO19878
 18 JUL 65
 G CO26103
 10 FEB 67
 H CO31959
 9 NOV 85
 K CO61381
 22 APR 87
 L CO7319-C
 19 SEP 92
 R.E.R. 26 DEC 98
 DRAWN
 G.H.

CHARACTERISTICS
OPERATING FORCE - - - - - 12-32 OZ.
RELEASE FORCE - - - - - 8 OZ. MIN.
PRETRAVEL - - - - - .219 MAX. (6°)
DIFFERENTIAL TRAVEL - - - .012 MAX.
DONOT OVERTRAVEL MORE THAN 25°
SWITCH-BASIC REPLACEMENT BA-2R-P4

ELECTRICAL DATA
CONTACT ARRANGEMENT S. P. D. T.
L23 20 A-125, 350 OR 480 VAC 10 A-125 VAC "L" 1 HP-125 VAC, 2 HP-250 VAC 1/2 A-125 VDC, 1/4 A-250 VDC

SCALE FULL
DO NOT SCALE PRINT
UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES ARE:
ONE PLACE (.01) ±.030
TWO PLACE (.00) ±.018
THREE PLACE (.000) ±.008
ANGLES 2
WEIGHT

- NOTE-
- (8) MOUNTING SCREW HOLES, 10-32 NF-2B THREADS X .219 REF DEEP.
 - 8-32 NC X .219 REF TERMINAL SCREWS AND CUPWASHERS.
 - EXPLOSION PROOF - UNDERWRITER'S LAB, INC. LISTING FOR HAZARDOUS LOCATIONS NEMA 7, CLASS 1, GROUPS C AND D, NEMA 9, CLASS II, GROUPS E, F AND G
 - EUROPEAN HAZARDOUS LOCATIONS DESIGNATION: Ex dIB + H2 T6 CATEGORY II 2 G
 - SEAL RATING: NEMA 1
 - EXTERNAL GROUND SCREW MAY BE ASSEMBLED TO ANY UNUSED MOUNTING SCREW HOLE ASSEMBLE PROVIDED SPLIT LOCKWASHER BETWEEN GROUND LUG AND HOUSING