



Schutzvermerk nach DIN 34 beachten  
Copyright reserved

19.01.2000

**Mechanical features**  
Enclosure: Thermoplast, glass fibre reinforced  
Cover: Thermoplast, glass fibre reinforced  
Actuator: Turret head (Zn-die cast), roller (thermoplast)

Ambient air temperature: -30°C up to +80°C  
Contact type: 1 NC-contact, 1 NO-contact

Mechanical life: 10x10<sup>6</sup> switch operations  
Switch frequency: max. 100/min  
Mounting: 4 x M5  
Connection type: 4 screw connections (M3.5)  
Cable entry size: 1 x Pg13.5  
Weight: approx. 0,24kg

**Electrical features**  
Max. Voltage: 500 V AC  
Max. enduring current: 1 th 10A  
Max. inrush current: according to IEC 947-5-1, AC 15, DC 13  
Standards: according to EN 60204; EN 60947-1; EN 60947-5-1  
Protection class (IP-Code): IP65 according to EN 60529; DIN VDE 0470 T1  
CSA: 10A 300V AC, A300 (same polarity)  
Short circuit protection: 10A slow-acting, 16A quick-acting

**Approach possibilities**  
By loosening 4 screws it is possible to turn the actuator through 90° so that 4 approach possibilities can be achieved.

**Remarks**  
The moving parts should be oiled periodically.  
The planned protection class (IP-Code) is valid only at closed cover  
when using at least equivalent cable gland.