XCSE7333 SAFETY INTERLOCK 300VAC 5A T-XCS

List Price \$602.00 USD

Availability Stock Item: This item is normally stocked in our distribution facility.

Technical Characteristics

Number of Poles	3-Pole
Supply Voltage	120V
Pilot Light	Orange LED - Green LED
Actuator Type	Key
Lock Method	Inserting Actuating Key
Enclosure Material	Metal
Height	5.75 Inches
Connection Type	(2) 0.5 Inch NPT (Conduit Entrance)
Enclosure Rating	NEMA 4/4X/12 - IP67
Ampere Rating	6A
Contact Operation	Slow Break (Break before Make)
Enclosure Type	Water tight, Dust tight and Corrosion resistant (Indoor/Outdoor)
Approvals	UL Listed File Number: E164353 CCN NKCR - CSA Certified File Number: LR4408794 Class 3211 03 - CE Marked
Contact Configuration	1 N.O.(staggered)/2 N.C.
Depth	1.73 Inches
Orientation	Actuating Key: Field Selectable - Electromagnet: Via conduit entrance
Maximum Voltage Rating	300VAC
Operating Temperature Range	-13 to 104 Degrees F
Terminal Type	Screw Clamp
Туре	XCSE

Shipping and Ordering

Category	22411 - Limit Switches, Heavy Duty, IEC, Type XCKJ
Discount Schedule	Т
GTIN	00785901719809
Package Quantity	1
Weight	2.81 lbs.
Availability Code	Stock Item: This item is normally stocked in our distribution facility.
Returnability	Υ
Country of Origin	FR

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

Generated: 04/28/2011 02:47:24

