XCSMP79L2

SAFETY INTERLOCK 300VAC 2.5A T-XCS

List Price \$128.00 USD

Availability Non-Stock Item: This item is not normally stocked in our distribution facility.

Technical Characteristics

Number of Poles	2-Pole
Ampere Rating	2.5A
Actuator Type	Key
Lock Method	Not Lockable
Height	3.42 Inches
Connection Type	Prewired (2m Cable)
Enclosure Rating	NEMA 4/4X/12 - IP67
Contact Operation	Slow Break
Approvals	UL Listed File Number: E164353 CCN NKCR - CSA Certified File Number: LR4408794 Class 3211 03 - CE Marked
Enclosure Type	Water tight, Dust tight and Corrosion resistant (Indoor/Outdoor)
Contact Configuration	2 N.C.
Depth	0.60 Inches
Enclosure Material	Plastic
Orientation	Actuating Key: Field Selectable - Electromagnet: Via conduit entrance
Maximum Voltage Rating	300VAC
Operating Temperature Range	-13 to 176 Degrees F
Type	XCSMP

Shipping and Ordering

Category	22411 - Limit Switches, Heavy Duty, IEC, Type XCKJ
Discount Schedule	Т
STIN	00785901632214
Package Quantity	1
Veight	0.25 lbs.
Availability Code	Non-Stock Item: This item is not normally stocked in our distribution facility.
Returnability	N
Country of Origin	JP

As standards, specifications, and designs change from time to time, please ask for confirmation of the information given in this document.

© 2011 Schneider Electric. All rights reserved.