

# TURCK

## Stainless Steel Front Face



Housing Style	Part Number	ID Number	Features	Sensing Range (mm)	Output
<b>30 mm - Embeddable, eurofast® Connection, Stainless Steel Front Face</b> 	Bi10-EM30F-AP6X-H1141	M4614537	<i>Stainless Steel Body and Face</i>	10	3-Wire DC PNP
<b>30 mm - Embeddable, eurofast Connection, Stainless Steel Front Face, Teflon Coated Barrel</b> 	Bi10-EMT30F-AP6X-H1141	M4614563	<i>Teflon Coated, Stainless Steel Body and Face</i>	10	3-Wire DC PNP
<b>30 mm - Embeddable, eurofast Connection, Stainless Steel Front Face, weldguard, Teflon Coated Barrel</b> 	Bi10-EMT30F-AP6X-H1141/S1589	M4614598	<i>Teflon Coated, Stainless Steel Body and Face, weldguard</i>	10	3-Wire DC PNP



Voltage	Switching Freq. (Hz)	Operating Current (mA)	Operating Temp. (°C)	Protection	Housing	Face	Power LED	Output LED	Mating Cordset	Wiring Diagram #	Wiring Diagrams
10-30 VDC	180	≤200	-25 to +80	IP 68 /IP 69K	SS	SS	N/A	YE	RKC 4T-*/S1587	1	<p>Diagram 1</p>
10-30 VDC	180	≤200	-25 to +80	IP 68 /IP 69K	SS/TC	SS/TC	N/A	YE	RKC 4T-*/S1587	1	
10-30 VDC	180	≤200	-25 to +80	IP 68 /IP 69K	SS/TC	SS/WG	N/A	YE	RKC 4T-*/S1587	1	

\* Length in meters.

Stainless Steel Front Face