



**Description**

Designed for use in a wide variety of production, batching and packaging applications. These 4 or 6 figure electromechanical predetermining counters count down from a preset number and activate a SPDT switch. Convenient preset controls and built-in manual reset with guard are standard. A surge absorbing circuit protects against damage due to voltage spikes. Heavy duty bail mount secures counter in place.

**Features**

- 4 or 6 figures
- Heavy duty mount
- SPDT switch

**Options**

- Voltages

**Specifications**

**Figures:** 4 or 6 figures, white on black, 0.16" [4mm] high  
**Reset:** Manual, or electric reset (min. 100ms - on, 1min - off)  
**Speed:** 600 counts/minute (min. 50ms - on, 50ms - off)  
**Voltages:** 115VAC, 24VDC  
 (+/-10%, but not to exceed 10 volts)  
**Power:** 5.5 watts count, 20 watts reset (nominal)  
**Mounting:** Bail

**Termination:** Screw type  
**Operating Life:** Beyond 100 million counts  
**Temp. Range:** -15°F to +140°F [-26°C to + 60°C]  
**Output Switch:** SPDT 5 Amp. @ 250 VAC resistive  
**Output Duration:** Until reset  
**Approvals:** UL Recognized, CE Compliant  
**Weight:** 10 oz. [284g]

**Models Description**

**B2-5804** 115VAC, 4 figure, manual reset  
**B2-5804/E2** 115VAC, 4 figure, 115VAC electric reset  
**B8-5804** 24VDC, 4 figure, manual reset  
**B8-5804/E8** 24VDC, 4 figure, 24VDC electric reset


**Models Description**

**B2-5806** 115VAC, 6 figure, manual reset  
**B2-5806/E2** 115VAC, 6 figure, 115VAC electric reset  
**B8-5806** 24VDC, 6 figure, manual reset  
**B8-5806/E2** 24VDC, 6 figure, 115VAC electric reset

\* Items in bold are normally in factory stock.

**Dimensions**

**Bail Mount**



Panel cutout: 2.17" x 2.17" [55.1 x 55.1]

**Applications**

