

## 3P-X-TELE-1-N1: Environmental & Industrial Sensor Monitoring Node

3<sup>rd</sup> Platform Telemetry Node provides an instant out-of-the-box solution to rapidly gain vision of your remote equipment.

Designed to accelerate the investigation and research into remote monitoring of field based or edge of network devices.

3<sup>rd</sup> Platform Telemetry single node:




### 3P-X-TELE-1-N1

Allows for data collection from remote equipment for monitor or alarm status, use patterns, reporting levels and output monitoring for integration and data manipulation.

Hardware supplied in DIN Rail format (but can be used in standalone mode) for ease of installation into industrial applications.

Kits are supplied with an SLA (service level agreement) and terms and conditions sign-up required, these cover fair usage on the Cellular Network SIM, and support.



- Three analog inputs: 0-10V, 4-20mA and PTC (thermistor)
- One digital Input
- Optional Backup Battery – Lithium ion
- RS232 interface for direct communication
- Mains Power failure alarm reporting via SMS or GPRS
- SIM included
- Expandable

#### Accessory Parts

#### 3P-TELE-1-N1

3<sup>rd</sup> Platform additional telemetry node and connection to an existing purchased kit "3P Telemetry Experience kit".



For more information, please contact [sales@3rdplatform.com](mailto:sales@3rdplatform.com)