



# Infresco Remote control

## IR-RC

X10729

### INTRODUCTION


This remote control has been designed to work with the Infresco IR. It allows the output of the controller to be turned up and down remotely. This allows the main controller to be mounted in any location but the IR controller must be in sight of the remote control to work.

### SPECIFICATIONS

Battery: 2 X AAA (Supplied)  
Dimensions: 160 x 45 x 20



### INSTALLATION



#### Display Features

### Non operational

- + Setting 0 to F Increase output with 10 output levels
- Setting F to 0 Decrease output with 10 output levels

#### Infresco IR Display

When display shows 't'

The Infresco is monitoring the ambient temperature and the ambient temperature remains above the trip level.

When display shows 'F'  
When the Decimal Point flashes  
When the Decimal Point is on

The Infresco is set to full output  
Transmitting from Remote hand set  
The Infresco is on standby.

RoHS Compliant  
Directive  
2002/95/EC

For Additional installation information see X10702

### CE MARKING

This family carries a "CE" marking. For more information see recommendations section and contact our sales desk. (See Declaration of Conformity)



### UNITED AUTOMATION LIMITED

1 Southport Business Park  
Kew  
Southport, PR8 4HQ  
ENGLAND

Tel: 0044 (0) 1704 – 516500 Main  
Tel: 0044 (0) 1704 – 516516 Sales  
Fax: 0044 (0) 1704 – 516501  
Enquiry@united-automation.com  
www.united-automation.com  
Date 05/11/99

Page No. 1 of 1 Issue 3

