



REVISIONS

DOC. NO. SPC-F004 \* Effective: 7/8/02 \* DCP No: 1398

DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
1453	A	RELEASED	JWM	8/27/03	JC	8/28/03	DJC	8/28/03



**FEATURES:**

- Quad Independent DC Output
- Four LED Display with 3 digits, selectable for two sets output voltage and current display simultaneously
- Auto Series, Parallel and Tracking Operation
- Constant Voltage and Constant Current Operation
- Low Ripple and Noise
- Overload and Reverse Polarity Protection
- Selectable for Continuous/Dynamic Load
- Output Enable/Disable Control
- Rotation speed of the fan is controlled by heatsink temperature



SPC-F004.DWG

TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	DRAWN BY:	DATE:	DRAWING TITLE:			
	Jeff McVicker	8/27/03	Dual Output, Digital Power Supply			
	CHECKED BY:	DATE:	SIZE	DWG. NO.	ELECTRONIC FILE	REV
	John Cole	8/28/03	A	72-7245	22H6396.dwg	A
APPROVED BY:	DATE:	SCALE:	U.O.M.:	SHEET:		
Daniel Carey	8/28/03	NTS	Millimeters	1 OF 2		

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

## **SPECIFICATIONS**

### **Output (CH1, CH2)**

Voltage: 0 ~ 30V

Current: 0 ~ 3A

Tracking Series Voltage: 0 ~ 60V

Tracking Parallel Current: 0 ~ 6A

### **CONSTANT VOLTAGE OPERATION (CH1, CH2)**

Line Regulation:  $\leq 0.01\% + 3\text{mV}$

Load Regulation:  $\leq 0.01\% + 3\text{mV}$  (rating current  $\leq 3\text{A}$ )

$\leq 0.02\% + 5\text{mV}$  (rating current  $> 3\text{A}$ )

Ripple & Noise:  $\leq 1\text{mVrms}$  5Hz ~ 1MHz

Recovery Time:  $\leq 100\mu\text{S}$  (50% Load change, Minimum load 0.5A)

### **CONSTANT CURRENT OPERATION (CH1, CH2)**

Line Regulation:  $\leq 0.2\% + 3\text{mA}$

Load Regulation:  $\leq 0.2\% + 3\text{mA}$

Ripple & Noise:  $\leq 3\text{mArms}$

### **TRACKING OPERATION (CH1, CH2)**

Tracking Error:  $\leq 0.5\% + 10\text{mV}$  of the Master

Series Regulation:  $\leq 300\text{mV}$

Load Regulation:  $\leq 0.01\% + 3\text{mV}$

Ripple & Noise:  $\leq 2\text{mVrms}$  5Hz ~ 1MHz

### **METER**

3 digits 0.5" LED display

Accuracy:  $\pm(0.5\% \text{ rdg} + 2 \text{ digits})$

### **INSULATION**

Chassis and Terminal:  $\geq \text{DC } 500\text{V} / 20\text{Megohms}$

Chassis and AC Cord:  $\geq \text{DC } 500\text{V} / 30\text{Megohms}$

### **POWER SOURCE**

AC 100V/120V/220V  $\pm 10\%$ , 230V  $\pm 10\% \sim -6\%$ , 50/60Hz

### **Dimensions & Weight:**

255mm(W) x 145mm(H) x 265mm(D), Approx. 7kg

### **ACCESSORIES**

Instruction manual, Power cord, and Test lead

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY.

SPC-F004.DWG

SIZE DWG. NO.

A

72-7245

ELECTRONIC FILE

22H6396.dwg

REV

A

DOC. NO. SPC-F004 \* Effective: 7/8/02 \* DCP No: 1398

SCALE: NTS

U.O.M.: INCHES [mm]

SHEET: 2 OF 2