


Visual Indicating Fuseholder

For $\frac{1}{4}$ " x $1\frac{1}{4}$ " (6.3mm x 32mm) Pin Indicating Fuses


HLD
HLD-HH

Dimensional Data



Catalog Symbol: HLD and HLD-HH
 Visual Indicating Fuseholder
 Ampere Rating: 15A
 Voltage Rating: 250V
 Temperature Rating (RTI): 130°C
 Agency Information:
 UL Recognized, HLD Guide IZLT2, File E14853

Punched Mounting Hole



Electrical Ratings

Symbol	Amps	Volts AC	Features
HLD	15	250	Solder terminals
HLD-HH	15	250	$\frac{1}{4}$ " quick-connect terminals

CE logo denotes compliance with European Union Low Voltage Directive (50-1000Vac, 75-1500Vdc). Refer to Data Sheet: 8002 or contact Bussmann Application Engineering at 314-527-1270 for more information.

General Information:

- For use with GBA and GLD fuses.
- Bayonet-type transparent knob permits visual indication of "opened" pin indicating fuses.
- Do not put tension on line (rear) terminal.

The only controlled copy of this Data Sheet is the electronic read-only version located on the Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.