

HRC cartridge fuses



Pack

Cat.Nos

Technical data and dimensions
(p. 80-81)

Cylindrical type gG

Conform to NF C 60-200 - 63-210/211
IEC 60269-1 and 2-1
Veritas approved

| | Without indicator | With indicator | Rating (Amps) | Voltage \pm (Volts) | Rupture capacity (Amps) | | |
|----|-----------------------|-----------------------|---------------|-----------------------|-------------------------|-----|---------|
| 10 | 133 94 | | 0.5 | 500 | 100 000 | | |
| 10 | 133 01 | | 1 | | | | |
| 10 | 133 02 | 134 02 | 2 | | | | |
| 10 | 133 04 | 134 04 | 4 | | | | |
| 10 | 133 06 | 134 06 | 6 | | | | |
| 10 | 133 08 | 134 08 | 8 | | | | |
| 10 | 133 10 | 134 10 | 10 | | | | |
| 10 | 133 12 | 134 12 | 12 | | | | |
| 10 | 133 16 | 134 16 | 16 | | | | |
| 10 | 133 20 | 134 20 | 20 | | | | |
| 10 | 133 25 | 134 25 | 25 | | | | |
| | Without striker | With striker | | | | 500 | 100 000 |
| 10 | 143 02 | | 2 | | | | |
| 10 | 143 04 | 145 04 | 4 | | | | |
| 10 | 143 06 | 145 06 | 6 | | | | |
| 10 | 143 10 | 145 10 | 10 | | | | |
| 10 | 143 16 | 145 16 | 16 | | | | |
| 10 | 143 20 | 145 20 | 20 | | | | |
| 10 | 143 25 | 145 25 | 25 | | | | |
| 10 | 143 32 | 145 32 | 32 | | | | |
| 10 | 143 40 | 145 40 | 40 | | | | |
| 10 | 143 50 ⁽¹⁾ | 145 50 ⁽¹⁾ | 50 | | | | |
| | | | | 500 | 100 000 | | |
| 10 | 153 04 | | 4 | | | | |
| 10 | 153 06 | | 6 | | | | |
| 10 | 153 10 | 155 10 | 10 | | | | |
| 10 | 153 16 | 155 16 | 16 | | | | |
| 10 | 153 20 | 155 20 | 20 | | | | |
| 10 | 153 25 | 155 25 | 25 | | | | |
| 10 | 153 32 | 155 32 | 32 | | | | |
| 10 | 153 40 | 155 40 | 40 | | | | |
| 10 | 153 50 | 155 50 | 50 | | | | |
| 10 | 153 63 | 155 63 | 63 | | | | |
| 10 | 153 80 | 155 80 | 80 | | | | |
| 10 | 153 96 | 155 96 | 100 | | | | |
| 10 | 153 97 ⁽¹⁾ | 155 97 ⁽¹⁾ | 125 | | | | |

(1) Overtopping described by standards

HRC cartridge fuses (continued)



Pack

Cat.Nos

Technical data and dimensions
(p. 80-81)

Cylindrical type aM (motor rated)

Conform to NF C 60-200 - EN 60269-1
IEC 60269-1

Veritas approved

| | Without striker | With striker | Rating (Amps) | Voltage \pm (Volts) | Rupture capacity (Amps) |
|----|-----------------|--------------|---------------|-----------------------|-------------------------|
| 10 | 120 01 | | 1 | 400 | 20 000 |
| 10 | 120 02 | | 2 | | |
| 10 | 120 04 | | 4 | | |
| 10 | 120 06 | | 6 | | |
| 10 | 120 08 | | 8 | | |
| 10 | 120 10 | | 10 | | |

Conform to NF C 63-210/211
IEC 60269-1, 2 and 2-1
Veritas approved

10 x 38 HRC

| | Without striker | With striker | Rating (Amps) | Voltage \pm (Volts) | Rupture capacity (Amps) |
|----|-----------------------|--------------|---------------|-----------------------|-------------------------|
| 10 | 130 92 | | 0.25 | 500 | 100 000 |
| 10 | 130 95 | | 0.50 | | |
| 10 | 130 01 | | 1 | | |
| 10 | 130 02 | | 2 | | |
| 10 | 130 04 | | 4 | | |
| 10 | 130 06 | | 6 | | |
| 10 | 130 08 | | 8 | | |
| 10 | 130 10 | | 10 | | |
| 10 | 130 12 | | 12 | | |
| 10 | 130 16 | | 16 | | |
| 10 | 130 20 ⁽²⁾ | | 20 | | |
| 10 | 130 25 ⁽²⁾ | | 25 | | |

14 x 51 HRC

| | Without striker | With striker | Rating (Amps) | Voltage \pm (Volts) | Rupture capacity (Amps) |
|----|-----------------------|-----------------------|---------------|-----------------------|-------------------------|
| 10 | 140 02 | 141 02 | 2 | 500 | 100 000 |
| 10 | 140 04 | 141 04 | 4 | | |
| 10 | 140 06 | 141 06 | 6 | | |
| 10 | 140 08 | 141 08 | 8 | | |
| 10 | 140 10 | 141 10 | 10 | | |
| 10 | 140 12 | 141 12 | 12 | | |
| 10 | 140 16 | 141 16 | 16 | | |
| 10 | 140 20 | 141 20 | 20 | | |
| 10 | 140 25 | 141 25 | 25 | | |
| 10 | 140 32 | 141 32 | 32 | | |
| 10 | 140 40 | 141 40 | 40 | | |
| 10 | 140 45 ⁽¹⁾ | 141 45 ⁽¹⁾ | 45 | | |
| 10 | 140 50 ⁽¹⁾ | 141 50 ⁽¹⁾ | 50 | | |

22 x 58 HRC

| | Without striker | With striker | Rating (Amps) | Voltage \pm (Volts) | Rupture capacity (Amps) |
|----|-----------------|--------------|---------------|-----------------------|-------------------------|
| 10 | 150 16 | 151 16 | 16 | 500 | 100 000 |
| 10 | 150 20 | 151 20 | 20 | | |
| 10 | 150 25 | 151 25 | 25 | | |
| 10 | 150 32 | 151 32 | 32 | | |
| 10 | 150 40 | 151 40 | 40 | | |
| 10 | 150 50 | 151 50 | 50 | | |
| 10 | 150 63 | 151 63 | 63 | | |
| 10 | 150 80 | 151 80 | 80 | | |
| 10 | 150 96 | 151 96 | 100 | | |
| 10 | 150 97 | 151 97 | 125 | | |

Neutral links

| | | |
|----|--------|------------|
| 10 | 123 00 | 8.5 x 31.5 |
| 10 | 133 00 | 10 x 38 |
| 10 | 143 00 | 14 x 51 |
| 10 | 153 00 | 22 x 58 |



(1) Overtopping described by standards
(2) Overtopping not described by standards