

## NTE572 Silicon Rectifier General Purpose, Fast Recovery

**Features:**

- Fast Switching
- Low Leakage
- Low Forward Voltage Drop
- High Current Capability
- High Current Surge
- High Reliability

**Maximum Ratings and Electrical Characteristics:** ( $T_A = +25^\circ\text{C}$  unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.)

Maximum Recurrent Peak Reverse Voltage .....	1000V
Maximum RMS Voltage .....	700V
Maximum DC Blocking Voltage .....	1000V
Maximum Average Forward Rectified Current (.375" (9.5mm) lead length, $T_A = +55^\circ\text{C}$ ) .....	6A
Peak Forward Surge Current (8.3ms single half sine-wave superimposed on rated load) ...	300A
Maximum Instantaneous Forward Voltage ( $I_F = 6\text{A DC}$ ) .....	1.3V
Maximum DC Reverse Current (At Rated DC Blocking Voltage, $T_A = +25^\circ\text{C}$ ) .....	10 $\mu\text{A}$
Maximum Full Load Reverse Current (Full Cycle Average .375" (9.5mm) lead length, $T_L = +55^\circ\text{C}$ ) .....	150 $\mu\text{A}$
Maximum Reverse Recovery Time (Note 1) .....	500ns
Typical Junction Capacitance (Note 2) .....	100pF
Operating Junction Temperature Range, $T_J$ .....	$-65^\circ$ to $+175^\circ\text{C}$
Storage Temperature Range, $T_{stg}$ .....	$-65^\circ$ to $+175^\circ\text{C}$

Note 1. Reverse Recovery Test Conditions:  $I_F = 500\text{mA}$ ,  $I_R = 1\text{A}$ ,  $I_{RR} = 250\text{mA}$ .

Note 2. Measured at 1MHz and applied reverse voltage of 4.0 volts.

