

# SS3 Series



## Controlled Avalanche Power Diodes




### Features:

- For surface mounted application.
- Metal to silicon rectifier, majority carrier conduction.
- Low forward voltage drop.
- Easy pick and place.
- High surge current capability.
- Epitaxial construction
- High temperature soldering: 260°C/10 seconds at terminals.

### Mechanical Data:

Case : Moulded plastic.  
Terminals : Solder plated.  
Polarity : Indicated by cathode band.

### SMC/DO-214AB



Dimensions : Inches (Millimetres)



### Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified. Single phase, half wave, 60Hz, resistive or inductive load. For capacitive load, derate current by 20%.

Type Number	Symbol	SS34	SS36	Unit
Maximum recurrent peak reverse voltage	$V_{RRM}$	40	60	V
Maximum RMS voltage	$V_{RMS}$	28	42	
Maximum DC blocking voltage	$V_{DC}$	40	60	
Maximum average forward rectified current at $T_L$ (See Figure 1)	$I_{(AV)}$	3.0		A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	$I_{FSM}$	100		
Maximum Instantaneous forward voltage (Note 1) at 3.0A	$V_F$	0.5	0.75	V
Maximum DC reverse current at $T_A = 25^\circ\text{C}$ at rated DC blocking voltage at $T_A = 100^\circ\text{C}$	$I_R$	0.5		mA
		20	10.0	
Typical thermal resistance (Note 2)	$R_{\theta JL}$	17		$^\circ\text{C/W}$
	$R_{\theta JA}$	55		
Operating temperature range	$T_J$	-55 to +125	-55 to +150	$^\circ\text{C}$
Storage temperature range	$T_{STG}$	-55 to +150		

#### Notes:

1. Pulse test with  $PW = 300\mu\text{sec}$ , 1% duty cycle.
2. Measured on PC Board with  $0.6 \times 0.6$ " (16 x 16mm) copper pad areas.

### Ratings and Characteristic Curves

Figure 1 Maximum Forward Current Derating Curve





Figure 2 Maximum Non-Repetitive Forward Surge Current



# SS3 Series

## Controlled Avalanche Power Diodes



Figure 3 Typical Forward Characteristics




Figure 4 Typical Reverse Characteristics




Figure 5 Typical Junction Capacitance





Figure 6 Typical Transient Thermal Impedance



# SS3 Series



## Controlled Avalanche Power Diodes

### Specifications

$I_F$ (AV) (A)	$T_C$ (°C)	$V_{RRM}$ (V)	$V_{FM}$ maximum (V)	$I_{RM}$ maximum (mA)	Package	Part Number
3	105	40	0.5	0.5	DO-214AB (SMC)	SS34
		60	0.75			SS36



# SS3 Series

## Controlled Avalanche Power Diodes



### Notes:

### International Sales Offices:

 <b>AUSTRALIA</b> – Farnell InOne Tel No: ++ 61 2 9645 8888 Fax No: ++ 61 2 9644 7898	 <b>FINLAND</b> – Farnell InOne Tel No: ++ 358 9 560 7780 Fax No: ++ 358 9 345 5411	 <b>NETHERLANDS</b> – Farnell InOne Tel No: ++ 31 30 241 7373 Fax No: ++ 31 30 241 7333	 <b>SWITZERLAND</b> – Farnell InOne Tel No: ++ 41 1 204 64 64 Fax No: ++ 41 1 204 64 54
 <b>AUSTRIA</b> – Farnell InOne Tel No: ++ 43 662 2180 680 Fax No: ++ 43 662 2180 670	 <b>FRANCE</b> – Farnell InOne Tel No: ++ 49 89 61 39 39 39 Fax No: ++ 33 474 68 99 90	 <b>NEW ZEALAND</b> – Farnell InOne Tel No: ++ 64 9 357 0646 Fax No: ++ 64 9 357 0656	 <b>UK</b> – Farnell InOne Tel No: ++ 44 8701 200 200 Fax No: ++ 44 8701 200 201
 <b>BELGIUM</b> – Farnell InOne Tel No: ++ 32 3 475 2810 Fax No: ++ 32 3 227 3648	 <b>GERMANY</b> – Farnell InOne Tel No: ++ 49 89 61 39 39 39 Fax No: ++ 49 89 613 59 01	 <b>NORWAY</b> – Farnell InOne Tel No: ++ 45 44 53 66 66 Fax No: ++ 45 44 53 66 02	 <b>UK</b> – BuckHickman InOne ++ 44 8450 510 150 ++ 44 8450 510 130
 <b>BRAZIL</b> – Farnell-Newark InOne Tel No: ++ 55 11 4066 9400 Fax No: ++ 55 11 4066 9410	 <b>HONG KONG</b> – Farnell-Newark InOne Tel No: ++ 852 2268 9888 Fax No: ++ 852 2268 9899	 <b>PORTUGAL</b> – Farnell InOne Tel No: ++ 34 93 475 8804 Fax No: ++ 34 93 474 5288	 <b>UK</b> – CPC ++ 44 8701 202 530 ++ 44 8701 202 531
 <b>CHINA</b> – Farnell-Newark InOne Tel No: ++86 10 6238 5152 Fax No: ++86 10 6238 5022	 <b>IRELAND</b> – Farnell InOne Tel No: ++ 353 1 830 9277 Fax No: ++ 353 1 830 9016	 <b>SINGAPORE</b> – Farnell-Newark InOne Tel No: ++ 65 6788 0200 Fax No: ++ 65 6788 0300	 <b>EXPORT</b> – Farnell InOne Tel No: ++ 44 8701 200 208 Fax No: ++ 44 8701 200 209 <b>For enquiries from all other markets</b>
 <b>DENMARK</b> – Farnell InOne Tel No: ++ 45 44 53 66 44 Fax No: ++ 45 44 53 66 06	 <b>ITALY</b> – Farnell InOne Tel No: ++ 39 02 93 995 200 Fax No: ++ 39 02 93 995 300	 <b>SPAIN</b> – Farnell InOne Tel No: ++ 34 93 475 8805 Fax No: ++ 34 93 474 5107	
 <b>ESTONIA</b> – Farnell InOne Tel No: ++ 358 9 560 7780 Fax No: ++ 358 9 345 5411	 <b>MALAYSIA</b> – Farnell-Newark InOne Tel No: ++ 60 3 7873 8000 Fax No: ++ 60 3 7873 7000	 <b>SWEDEN</b> – Farnell InOne Tel No: ++ 46 8 730 50 00 Fax No: ++ 46 8 83 52 62	

<http://www.farnellinone.com>  
<http://www.buckhickmaninone.com>  
<http://www.cpc.co.uk>

**Disclaimer** This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp is the registered trademark of the Group. © Premier Farnell plc 2004.

