


Band Switching Diodes



9612009

MECHANICAL DATA

Case: QuadroMELF SOD-80

Weight: approx. 34 mg

Cathode band color: black

Packaging codes/options:

GS18/10K per 13" reel (8 mm tape), 10K/box

GS08/2.5K per 7" reel (8 mm tape), 12.5K/box

FEATURES

- Silicon planar diodes
- Low dynamic forward resistance
- Low diode capacitance
- High reverse impedance
- QuadroMELF package
- AEC-Q101 qualified
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC


RoHS
COMPLIANT

APPLICATIONS

- Band switching in VHF-tuners

PARTS TABLE

PART	TYPE DIFFERENTIATION	ORDERING CODE	REMARKS
BA982	$V_R = 35\text{ V}$, r_f at $I_F 3\text{ mA} = \text{max. } 0.7\ \Omega$	BA982-GS18 or BA982-GS08	Tape and reel
BA983	$V_R = 35\text{ V}$, r_f at $I_F 3\text{ mA} = \text{max. } 1.2\ \Omega$	BA983-GS18 or BA983-GS08	Tape and reel

ABSOLUTE MAXIMUM RATINGS ⁽¹⁾

PARAMETER	TEST CONDITIONS	SYMBOL	VALUE	UNIT
Reverse voltage		V_R	35	V
Forward continuous current		I_F	100	mA

Note
⁽¹⁾ $T_{\text{amb}} = 25\text{ }^\circ\text{C}$, unless otherwise specified

THERMAL CHARACTERISTICS ⁽¹⁾

PARAMETER	TEST CONDITION	SYMBOL	VALUE	UNIT
Junction to ambient air	On PC board 50 mm x 50 mm x 1.6 mm	R_{thJA}	500	K/W
Junction temperature		T_j	150	$^\circ\text{C}$
Storage temperature range		T_{stg}	- 55 to + 150	$^\circ\text{C}$

Note
⁽¹⁾ $T_{\text{amb}} = 25\text{ }^\circ\text{C}$, unless otherwise specified

ELECTRICAL CHARACTERISTICS ⁽¹⁾

PARAMETER	TEST CONDITION	PART	SYMBOL	MIN.	TYP.	MAX.	UNIT
Forward voltage	$I_F = 100\text{ mA}$		V_F			1000	mV
Reverse current	$V_R = 20\text{ V}$		I_R			50	nA
Diode capacitance	$f = 100\text{ MHz}$, $V_R = 1\text{ V}$		C_{D1}			1.5	pF
	$f = 100\text{ MHz}$, $V_R = 3\text{ V}$	BA982	C_{D2}			1.25	pF
		BA983	C_{D2}			1.2	pF
Dynamic forward resistance	$f = 200\text{ MHz}$, $I_F = 3\text{ mA}$	BA982	r_{f1}			0.7	Ω
		BA983	r_{f1}			1.2	Ω
	$f = 200\text{ MHz}$, $I_F = 10\text{ mA}$	BA982	r_{f2}			0.5	Ω
		BA983	r_{f2}			0.9	Ω

Note
⁽¹⁾ $T_{\text{amb}} = 25\text{ }^\circ\text{C}$, unless otherwise specified

TYPICAL CHARACTERISTICS $T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified




Fig. 1 - Dynamic Forward Resistance vs. Forward Current






Fig. 2 - Diode Capacitance vs. Reverse Voltage

PACKAGE DIMENSIONS in millimeters (inches): **QuadroMELF SOD-80**



Created - Date: 03.November.2003
 Rev. 11 - Date: 07.June.2006
 Document no.:6.560-5006.01-4
 96 12071



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.