

# ES-257 ETHERNET TO SERIAL DEVICE SERVER

## Ethernet 2xRS232

CONNECT, CONFIGURE, CONTROL YOUR SERIAL DEVICES



### Description

Ethernet to Serial device server providing access to two RS232 serial ports. Up to 230,400 data transfer rates, coupled with 1Mbit/s line drivers deliver uncompromising performance. Our ES range provides a simple, instant cable replacement providing network integration.

**Windows Users** - Our Boost.LAN driver gives you local COM ports, retaining existing software applications on your network and allowing you to connect over larger distances. Our ES products are simple, instant cable replacement providing network integration on Windows 7 and Windows XP. Can install on any COM Port from COM1 to COM255 and remembers your COM Port assignment on reboots.

**Web Interface Users (Linux/Apple OS/Android)** - Alternatively access the device via TCP/IP socket from any networked device. Configure options via web interface.

Extend your reach! Remote serial devices with local control.

With Brainboxes industry renowned Lifetime Warranty\* and Lifetime Support!


### Features

- Max baud rate 230,400
- 10/100Base TX Ethernet port
- User friendly interface, simple to use, powerful in operation
- Web configuration and RFC2217 compliant interface for non-Windows users
- Rugged metal enclosure
- LED status indication
- Optional DIN rail mounting kit
- Power Supply included
- Power input 5-30V DC
- Simple operation for each and every operating system!

### Example Application



## Box Information



All dimensions in mm

## Key

- 1 - Power Input
- 2 - Reset button for device
- 3 - Ethernet port - 10/100 Mega bits/second

## Box Dimensions

- Size - 90x62x25 mm (not including mounting ears or connectors)
- Size - 120x80x25 mm (including mounting ears or connectors)

## LED Information

### Status LED

- Flashing Green: Device Ready
- Flashing Yellow: Changing Settings
- Flashing between Red & Green: Querying IP
- Flashing Green/Red: User performing Hard Reset
- Flashing between Green & Red/Yellow: IP address diagnostic
- Flashing between Green & Yellow: Initialization diagnostic

### Serial Port LEDs

- Green light on: Port Open
- Flashing Green: Data RX / TX

### Ethernet LED

- Green light on: Link Established
- Flashing Green: Data RX / TX

## Port

- Ports**: RS232
- Connector**: DB9 connector -- 9 Pin Male
- Power Input**: 5 - 30V DC input, reverse polarity protected

## Port Settings - RS232

Baud Rate	230,400
Data Bits	5,6,7 or 8
Parity	Odd, Even, None, Mark or Space
Stop Bits	1, 1.5 or 2
Flow Control	RTS/CTS, DSR/DTR, XON/XOFF
Tx/Rx Modes	Point to Point

## Port Settings - Ethernet

Data Rate	10/100 Mega bits/second
Cabling	Normal / Crossover auto-sensing (Auto-MDIX)

## Product Information

Power Consumption	awaiting
Product Weight	awaiting Kg

## Environmental

Operating Temperature	0 to 55°C
Storage Temperature	-20 to 85°C
Ambient Relative Humidity	5 to 95% (non-condensing)

## Software

Network Protocols	ICMP, IP, TCP, UDP, DHCP, BOOTP, Telnet, HTTP, RFC2217
Configuration Options	Windows Utility, Web Interface
OS Compatibility	Microsoft Windows 7 / Windows Server 2008 32 bit & 64 bit Editions / Windows Vista 32 bit & 64 bit Editions / Windows Server 2003 32 bit & 64 bit Editions / Windows XP 32 bit & 64 bit Editions / Microsoft Windows 2000 / Fully RFC2217 compliant / Interface for other OS's & Linux
Connection to Network	Ethernet 10BaseT / 100BaseTX

## Approvals

Industry Approvals	WEEERoHS EMC: CE
Microsoft Approvals	Microsoft Certified Gold Partner
Microsoft Signed Drivers	Windows 7 32 bit & 64 bit Editions Windows Server 2008 32 bit & 64 bit editions Windows Vista 32 bit & 64 bit editions Windows XP 32 bit & 64 bit editions



## Packing Information

Packaging	Installation CD including manual, Microsoft signed drivers & utilities
Device	Ethernet 2xRS232
Accessory Items	DIN-Rail Mounting Kit - MK-048 Power Supply (UK) - PW-844 Power Supply (EU) - PW-811
Packaged Weight	awaiting Kg
Packaged Dims	awaiting mm

## Product Support

### Warranty Support

Lifetime - online registration required

Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team



## Additional Information

### OEM option

Available for bulk buy OEM

### Made In


Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards 'Manufacturer of the Year'

### Customisable

Brainboxes operate a 'Perfect Fit Custom Design' policy for volume users. More info: [sales@brainboxes.com](mailto:sales@brainboxes.com)

## Accessory Items

### ORDER CODE - DIN-Rail Mounting Kit - MK-048



### ORDER CODE - Power Supply (UK) - PW-844 Power Supply (EU) - PW-811

