

RoHS Compliant



US-346

USB 4xRS422/485 1MBaud

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Description

USB to Serial providing four RS422/485 serial ports. Up to 921,600 data transfer rates and the 128 byte deep transmit and 384 byte receive FIFOs, coupled with 1Mbit line drivers deliver uncompromising performance on your laptop/PC.

USB to serial is the quick low cost way to connect your computer to a serial comms enabled device. Boost software gives industry leading functionality and compatibility.

These products do away with traditional issues with USB technology so you can buy with confidence!

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit and 64 bit editions
- Windows Vista 32 bit and 64 bit editions
- Windows XP 32 bit & 64 bit editions



As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.

Features

- 4 port RS422/485
- USB
- 128 Byte Tx and 384 Byte Rx FIFOs
- Up to 921,600 Baud
- 4xDB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



US-346:
USB 4xRS422/485
1MBaud



ORDER






Description
USB 4xRS422/485 1MBaud
USB Cable & Power Supply

Code
US-346



USB 4xRS422/485 1MBaud

US-346: Full Specification

Port 	Ports Connector FIFO size Operating Distance Cable	4 x RS422/485 4xDB9 connector (9 Pin Male) 384 RX FIFO + 128 TX FIFO RS422/485 Standard (4000 ft : 1200 metres) USB Cable (Powered via industrial locking connector with 5V 3A power adaptor - supplied)
Port Settings 	Baud Rate Data Bits Parity Stop Bits Flow Control Tx/Rx Modes	921,600 7 or 8 Odd, Even, None, Mark or Space 1 or 2 RTS/CTS, XON/XOFF Full Duplex, Half Duplex Autogating
Interface	OS Compatibility BUS	Microsoft Windows 7 32bit & 64bit Editions Windows Vista 32 bit & 64 bit Editions Windows XP 32 bit & 64 bit Editions USB :
Approvals 	Other Approvals Microsoft Approvals	WEEE RoHS EMC: CE Microsoft Certified Gold Partner Microsoft Certified Gold Partner
General	PCB Layers Power Consumption Weight Size	4 500mA 0.650 Kg 215x32x120 mm
Box Content	Packaging Card	Installation CD (including manual, Microsoft signed drivers & utilities) USB 4xRS422/485 1MBaud
Product Support 	Warranty Support	Lifetime (online registration required) Lifetime Web, Email and Phone Support from fully qualified, friendly staff who work in and alongside the Product Development Team
Additional 	OEM option Made In Customisable	Available for bulk buy OEM Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year" Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Datasheet Version: 4.37 Published on: 2009/12/17