


PT-9700PC

TZ-Tape



PC connectable Desktop Labelling machine



Copy

**Catalogue Spec**

- Print Tested to the extreme labels up to 36mm
- Fast Print Speed
- Comes with Free Tape and Power Adaptor
- Built in automatic cutter enables accurate tape length

## **PT-9700PC**

**Colour:** Light Grey and Pearl White

**Tape widths:** Machine accepts current range of HG & TZ Tapes:

- 3.5mm to 36mm (TZ Tapes)
- \*12mm to 36mm (HG Tapes)

**Tape inclusion:**

HG-261 36mm Black on white (8 Metre length) tape

**Keyboard:** N/A

## Hardware

| PRINTING              | PT-9700PC  |
|-----------------------|--|
| Dimensions            | 116mm(W) x 192.7mm(D) x 140mm(H)   |
| Design                | Cube   |
| Weight                | 1.57kg   |
| Housing Color         | Light Gray & Pearl White   |
| Keyboard              | Not available  |
| Number of Keys        | 2(Power On/Off, Feed and Cut)  |
| Tape Cutter           | Auto Full Cutter, Auto Half Cutter (Laminated tape only)   |
| Power                 | AC adaptor (AD9100ES) (Enclosed)   |
| Display               | Not available  |
| Panel LED lamp        | Red For Error status<br>Green For Ready status   |
| USB A lamp            | None   |
| LAN LED lamp          | None   |
| Attachments           | CD-ROM [P-touch Editor 5.0 for Windows, P-touch Editor 5.0 for Mac, Printer Driver, Software User's Guide, P-touch Template tools, ESC/P tools]<br>User's guide<br>TZ tape(24mm Black on White Laminated Tape) |
| Tape Cartridge        | TZ Tape, HG Tape   |
| Tape width variations | TZ 3.5-36mm, HG Tape 6-36  |
| Print Method          | Thermal transfer   |
| Max. Print Height     | 27.1mm   |

|                        |  |
|------------------------|--|
| Print Speed(tentative) | Maximum. 20mm / sec (For TZ/AL tape)<br>Maximum. 52mm / sec (For high-speed mode of HG tape only)<br>Maximum. 80mm / sec (For high-speed draft mode of HG tape only) |
| Print Head             | 360 dpi/384 dots   |
| Print resolution       | 360dpi( TZ / AL tape)<br>360dpi x 720dpi(For high resolution mode of HG tape only)<br>360dpi x 180dpi(For high speed mode of HG tape only)                           |
| Cutter Sensor          | Yes  |
| Tape End Sensor        | Yes  |
| Cover Open Sensor      | Yes  |
| Tape sensor            | Yes  |
| USB Function Interface | USB2.0 Full Speed  |
| RS-232C Interface      | Yes  |
| USB Host Interface     | N/A  |
| LAN Interface          | N/A  |
| ESC/P Printing         | Yes  |
| USB ID switching       | N/A  |

|             |              |
|-------------|--------------|
| Temperature | 10°C to 35°C |
| Humidity    | 20% to 80%   |