

Professional Labeling with a Difference

► Labels that Stick ► Easy to Use ► Saves Time and Money



ID PAL Labeling Tool

America*
tional*
a

^{*} Includes full label cartridge (PAL-750-439)

ACCESSORIES

Part Number	Description
81002 IDPAL-AC	ID PAL AC Adapter
81003 IDPAL-IG	ID PAL Impact Guards
81004 IDPAL-HC	ID PAL Hardside Carrying Case

SYMBOLS

Character	Symbol	Character	Symbol	Character	Symbol	
A	!	K	,	U	~	
В	@	L		V	2	
С	#	M	и	W	ф	
D	\$	N	/	Х	÷	
E	%	0	\	4	(
F	&	Р	۰	5	C ^F	
G	*	Q	_	6	(D	
Н	(R	±	7	-	
1)	S	1	8	+	
J	:	Т	Ω	9	=	

Prints as 📲 -

Press + Character

ID PAL is an affordable, easy-to-use, portable thermal transfer printer designed for the field, not the office. The rugged design has been tested to withstand harsh environments and a tough four foot drop test to concrete.

ID PAL uses Brady high performance labeling materials. The labels stay in place on your toughest surfaces, from wire and cable to highly textured plastic. As a result ID PAL eliminates the confusion caused by faded, smeared or poorly written labels, or labels that fall off leaving unidentified wires.

- Prints Brady-quality labels
- ► Easy-to-peel labels
- Fits great in your hand
- Job-tough construction
- Easy-to-see bright red color
- Quick, top-load, drop-in cartridge
- ► Built-in industrial cutter
- Intuitive keyboard with electrical and datacomm symbols
- Special wire marking mode with 10 preset lengths
- Prints upper and lower case characters
- Multiple line printing and serialization
- Automatic shut-off
- Six month warranty (12 months if registered)

SPECIFICATIONS

Print method:	Thermal transfer (non smearing)
Weight:	1.2 lbs. (0.55 kg) with batteries and tape cartridge included
Dimensions (L x W x H):	9.0 x 4.5 x 2.5 inches (228.6 x 114.3 x 63.5 mm)
Power source:	6 AA-size batteries print over 3500 1" (25.4 mm) labels
Operating temperature:	40° - 120° F (4° - 49° C)
Agency Approvals:	FCC Class A approved

FIVE FONT SIZES

	7	POINT
_	10	POINT
	14	POINT
	20	POINT
	28	POINT



LABELS FOR MULTIPLE APPLICATIONS **Choose from Three Label Types WIRE**



- Built-in leader for wrapping wire/cable
- ► Choose from 10 pre-programmed lengths: 0.75", 1", 1.2", 1.5", 2", 2.5", 3", 4", 5", 6"

BANNER



SCREW 1/4-28 2"

> Prints up to two lines of text

GENERAL




Prints up to four lines of text



EASY-PEEL LABEL

Oversized liner allows easy label removal

LESS LABEL WASTE RESULTS IN MORE LABELS



LABEL CARTRIDGE SELECTION CHART

		Max. Service		Label Width		Roll Length	Agency
Application	Material/Color	Temperature	3/8" (9mm)	1/2" (12mm)	3/4" (9mm)	Feet (m)	Approvals
— • ···· ···	Nylon Cloth B-499 / Black on White	194 (90) 30 days	PAL-375-499*	PAL-500-499+	PAL-750-499*	19' (5.8)	⊕ ⊕
— • • • • • • • • • • • • • • • • • • •	Vinyl B-439 / Black on White*	104 (40) 30 days	PAL-375-439+	PAL-500-439+	PAL-750-439+	21' (6.4)	(h) (f) ·
	Polyester B-430 / Black on Clear	212 (100) 30 days	PAL-375-430+	PAL-500-430+	PAL-750-430+	21' (6.4)	(h) (f)
	Polyester B-423 / Black on White	248 (120) 30 days	PAL-375-423+	PAL-500-423+	PAL-750-423+	21' (6.4)	(J) (∰• <u>RGR</u>

Plus... each cartridge comes preloaded with its own application-specific ribbon.

- Available in other colors
- + Catalog Number

Application Key

Smooth/Flat Surface

Textured Surface Wire/Cable/Curved Surface Highly Textured Surface



Identification Solutions & Specialty Tapes

www.bradyid.com

Australia 1-800-620-816 Belgium 32-(0)-152-457-811 Brazil 55-11-3686-4720 Canada 1-800-263-6179 China (Beijing) 86-10-6517-1260 China (Wuxi) 86-510-528-2222 England 44-(0)-1295-228-200 France 00-33-1-69-29-67-00

WORLDWIDE LOCATIONS

Germany 49-(0)-607-196-03 Hong Kong 852-2359-3149 Italy 39-02-967-00-507 Japan 81-45-461-3600 Korea 82-2-400-8418 Latin America 1-414-540-5560 Malaysia 60-4-283-3980 Mexico 525-399-6963

New Zealand 61-2-8717-2200 New Zealand 61-2-8717-220 Philippines 632-658-2077 Singapore 65-775-2077 Sweden 46-(0)-859-005-730 Taiwan 88-(6)-2-2345-1430 Thailand 66-2-943-0777 U.S.A. 1-800-537-8791



www.bradyidpal.com

©2002 BRADY Worldwide, Inc. Printed in U.S.A. Specifications subject to change without notice. All rights reserved. Y95178B 3-KK-02-VAM-10 Effective 3-02 AN ISO REGISTERED COMPANY