







### **RoHS** Compliant



# PCIe 2xRS422/485 1MBaud

### "SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"

PX-313



#### Features

- 2 port RS422/485
- PCI Express x1, x4, x8 & x16 lane slots socket size
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

#### Options



PX-313: PCle 2xRS422/485 1MBaud

#### Description

PCI Express Card providing two RS422/485 serial ports. Up to 921,600data transfer rates and the 128 byte deep transmit and 128 bytereceive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromisingperformance on your PC.

PCI Express is the latest standard in PC connectivity.

With Brainboxes' industry renowned Lifetime Warranty and Lifetime Support!

#### Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Server 2008 32 bit & 64 bit Editions
- Windows Vista 32 bit and 64 bit editions
- Windows Server 2003 32 bit & 64 bit Editions
- Windows XP 32 bit & 64 bit editions



As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.



ORDER Description PCIe 2xRS422/485 1MBaud

Code PX-313

## +44(0) 151 220 2500 sales@brainboxes.com www.brainboxes.com

PX-313

## PCIe 2xRS422/485 1MBaud

### PX-313: Full Specification

Port	Ports	2 x RS422/485
Pin 1 TXD- RS422/485 Pinout (9 pin)	Connector	DB9 connector (9 Pin Male)
Pin 2 TXD+ 1 5 Pin 3 RTS- 1 1	FIFO size	128  RX FIFO + 128  TX FIFO
Pin 4 RTS+ Pin 5 GND	Operating Distance	RS422/485 Standard (4000 ft : 1200 metres)
Pin 7 RXD+	Cable	No Cable; Integrated Connector
Pin 8 CTS- Pin 9 CTS+ 6 9		
Port Settings	Baud Rate	921,600
921,600	Data Bits	5,6,7 or 8
$\rightarrow$ $\rightarrow$ $\rightarrow$ $\rightarrow$	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1, 1.5 or 2
	Flow Control	RTS/CTS DSR/DTR XON/XOFF
	Tx/Rx Modes	Full Duplex, Half Duplex Autogating
Interface	OS Compatibility	Windows Server 2008 32 bit & 64 bit Editions
PCI>>		Windows Vista 32 bit & 64 bit Editions Windows Server 2003 32 bit & 64 bit Editions
PCI		Windows XP 32 bit & 64 bit Editions
		Microsoft Windows 2000
	BUS	PCI Express x1, x4, x8 & x16 lane slots :
Approvals	Other Approvals	WEEE ROHS METL EMC: CE
	Microsoft Approvals	Microsoft Certified Gold Partner
MET		Windows Server 2008 32 bit & 64 bit editions Windows Vista 32 bit & 64 bit editions
RoHS La cus		Windows Server 2003 32 bit & 64 bit editions Windows XP 32 bit &
		64 bit editions
General	PCB Layers	4
	Power Consumption	380mA @ 3.3V
	Weight	0.06 Kg
	Size	100x20x120 mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	PCIe 2xRS422/485 1MBaud /
		No Cable; Integrated Connector
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume
Manufacturer of the Year Nade in the UK		users. More Info: sales@brainboxes.com

Datasheet Version: 3.79 Published on: 2009/8/25