













# RoHS Compliant



# PX-320/ PX-324

## LP PCle 1xRS422/485 1MBaud

## "SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



## **Features**

- 1 port RS422/485
- PCI Express x1, x4, x8 & x16 lane slots socket size
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

#### **Options**



LP PCIe 1xRS422/485 1MBaud

PX-324 PCIe 1xRS422/485 1MBaud



### Description

PCI Express Card providing one RS422/485 serial port. Up to 921,600 data transfer rates and the 128 byte deep transmit and 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC.

PCI Express is the latest standard in PC connectivity.

With Brainboxes' industry renowned Lifetime Warranty and Lifetime Support! PX-320 - Low profile version; PX-324 - Standard profile version

#### Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Server 2008 32 bit & 64 bit Editions
- Windows Vista 32 bit and 64 bit editions
- Windows Server 2003 32 bit & 64 bit Editions
- Windows XP 32 bit & 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.

























ORDER Description

LP PCIe 1xRS422/485 1MBaud PCIe 1xRS422/485 1MBaud

Code PX-320

PX-324



# LP PCle 1xRS422/485 1MBaud

PX-320/ PX-324: Full Specification

174-520/ 174-524. Tuli Speci	rication	
Port	Ports	1 x RS422/485
Pin 1 TXD- RS422/485 Pinout (9 pin)	Connector	DB9 connector (9 Pin Male)
Pin 2 TXD+ 1 5 Pin 3 RTS- 1	FIFO size	128 RX FIFO + 128 TX FIFO
Pin 4 RTS+	Operating Distance	RS422/485 Standard (4000 ft : 1200 metres)
Pin 6 RXD- Pin 7 RXD+ Pin 8 CTS- Pin 9 CTS+	Cable	No Cable; Integrated Connector
Port Settings	Baud Rate	921,600
921,600	Data Bits	5,6,7 or 8
<b>&gt; &gt; &gt; &gt;</b>	Parity	Odd, Even, None, Mark or Space
baud	Stop Bits	1, 1.5 or 2
	Flow Control	RTS/CTS DSR/DTR XON/XOFF
	Tx/Rx Modes	Full Duplex, Half Duplex Autogating
	,	
Interface	OS Compatibility	Windows Server 2008 32 bit & 64 bit Editions
		Windows Vista 32 bit & 64 bit Editions
PCI>>> express		Windows Server 2003 32 bit & 64 bit Editions Windows XP 32 bit & 64 bit Editions
		Microsoft Windows 2000
	BUS	PCI Express x1, x4, x8 & x16 lane slots :
Approvals	Other Approvals	WEEE ROHS METL EMC: CE
Αρριοναίο	Microsoft Approvals	Microsoft Certified Gold Partner
RoHS (MET)	Wilelesoft Approvals	Windows Server 2008 32 bit & 64 bit editions Windows Vista 32 bit & 64 bit editions
cous		Windows Server 2003 32 bit & 64 bit editions Windows XP 32 bit & 64 bit editions
General	PCB Layers	4
	Power Consumption	380mA @ 3.3V
	Weight	0.043 Kg
	Size	105x20x80 mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	LP PCle 1xRS422/485 1MBaud / PCle 1xRS422/485 1MBaud
		No Cable; Integrated Connector
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5  Torogen Extraords Industry Pared	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Datasheet Version: 3.79 Published on: 2009/8/25