













RoHS Compliant



PX-387

PCle 1 x RS422/485 1MBaud Opto Isolated

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



Features

- 1 port RS422/485
- PCI Express x1, x4, x8 & x16 lane slots socket size
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



PX-387: PCIe 1 x RS422/485 1MBaud Opto Isolated

Description

PCI Express Card providing one opto isolated RS422/485 serial port. Up to 921,600 data transfer rates and the 128 byte deep transmitand 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC.

PCI Express is the latest standard in PC connectivity.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows Server 2008 32 bit & 64 bit Editions
- Windows Vista 32 bit and 64 bit editions
- Windows Server 2003 32 bit & 64 bit Editions
- Windows XP 32 bit & 64 bit editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.





















ORDER

Description

PCIe 1 x RS422/485 1MBaud Opto Isolated

Code PX-387



PCle 1 x RS422/485 1MBaud Opto Isolated

PX-387: Full Specification

Port	Ports	1 x RS422/485
Pin 1 TXD- RS422/485 Pinout (9 pin)	Connector	DB9 connector (9 Pin Male)
Pin 2 TXD+ 1 5 Pin 3 RTS- 1	FIFO size	128 RX FIFO + 128 TX FIFO
Pin 4 RTS+	Operating Distance	RS422/485 Standard (4000 ft : 1200 metres)
Pin 6 RXD- Pin 7 RXD- Pin 8 CTS- Pin 9 CTS+ 6 9	Cable	No Cable; Integrated Connector
Port Settings	Baud Rate	921,600
921,600 > > > > > > > > > > > > > > > > > > >	Data Bits	5,6,7 or 8
	Parity	Odd, Even, None, Mark or Space
	Stop Bits	1, 1.5 or 2
	Flow Control	RTS/CTS DSR/DTR XON/XOFF
	Tx/Rx Modes	Point to Point
Interface	OS Compatibility	Windows Server 2008 32 bit & 64 bit Editions
PCI≫		Windows Vista 32 bit & 64 bit Editions Windows Server 2003 32 bit & 64 bit Editions
EXPRESS		Windows XP 32 bit & 64 bit Editions
		Microsoft Windows 2000
	BUS	PCI Express x1, x4, x8 & x16 lane slots:
Approvals	Other Approvals	WEEE ROHS EMC: CE Microsoft Certified Gold Partner
	Microsoft Approvals	Microsoft Certified Gold Partner
RoHS CE		Windows Server 2008 32 bit & 64 bit editions Windows Vista 32 bit & 64 bit editions
		Windows Server 2003 32 bit & 64 bit editions Windows XP 32 bit &
		64 bit editions
General	PCB Layers	4
	Power Consumption	awaiting
	Weight	0.063 Kg
	Size	160x120x20 mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	PCIe 1 x RS422/485 1MBaud Opto Isolated
		No Cable; Integrated Connector
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5 Europea Bettronicis Industry Naudo	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Datasheet Version: 3.75 Published on: 2009/7/24