

Sentry RB4X12/24/2 Standard Battery and RB4X12/24/2 Long Life Battery



CE – Certified to EMC Directive 89/336/EEC.
 Complies with low voltage directive 2006/95/EC.
 High voltage transient and polarity reversal protection fitted.
 Operating temperature: -20°C to +50°C.



IP65	1 kg nominal

RB4X12/24/2 Std (4hrs flash time – nominal)	10cd	64/min	single flash
RB4X12/24/2 Long Life (6hrs flash time – nominal)	10cd	64/min	single flash

Features:

A stand-alone rechargeable battery powered Xenon beacon.

- Compact – 160mm diameter, 190mm high
- Replacement lenses available: amber, red, blue, green or clear
- Supplied with 12/24V charging lead, 230Vac mains charging option
- 12 months' guarantee
- Weatherproof to IP65

Materials:

Polycarbonate lens, ABS base.

2W Standard	420033
2W Long Life	420035

Beacon Accessories

Reference	Description	Part Number	LP Xenon LP-LED	LT Xenon LT-LED LT2-LED	RB Series Husky Pup Husky Pup2	MX-LED	Hedgehog (Xenon/LED) Mayday	LB Series	EL Series
FX1	Mounting Box	521001	✓						
FX2	Mounting Base	521002	✓	✓					
FX9	Protector Guard	521033			✓	✓			
FX10	Protector Guard	521021							✓
FX12	Single Bolt Kit	521019							✓
FX14	Mounting Bracket	521018			✓	✓	✓	✓	✓
FX23	Protector Guard	521040					✓		
FX24	Surface Mount / Side Entry Kit	521043					✓		
FX28	Cable Entry Plinth	521052			✓	✓			✓
FX29	Sounder Plinth (Multivoltage)	521047			✓				
FX32	DC Sounder plus FX28	521060			✓	✓			✓
FX33	AC/DC Sounder plus FX28	521070			✓	✓			✓
FX37	Protector Guard	521053						✓	
FX38	Mounting Pole with Sounder	521058	✓	✓					
FX39	Mounting Pole	521059	✓	✓					
FX40	Mounting Bracket	521034	✓	✓					



Beacons shown above are not included with accessories.