

693

LED Signal Tower Kompakt 36 in metal design



- Clear domes ensure signalling effect even in direct sunlight
- Plastic housing with aesthetic metal coating
- LED Permanent light elements with life duration up to 50,000 hours
- Simplified ordering through ready-assembled tower
- 36 mm diameter
- Can be operated with PLC control system
- Available with user-friendly plug connection

TECHNICAL SPECIFICATIONS:

Dimensions (Diameter x Height):	2 tier: 36 x 113 mm 3 tier: 36 x 147 mm
Housing:	Housing parts PC
Fixing:	Base mounting Tube mounting Bracket mounting
Connection:	cable, 2 m long, M12 plug, each with adapter M25 / M20 for fixing rubber seal
Operating voltage:	24 V DC
Current consumption:	40 mA per tier
Starting current:	< 500 mA can be triggered via PLC

ORDER SPECIFICATIONS:

		Order no.	Connection type
2 tier	red/green	693 080 55	cable
	red/yellow	693 090 55	cable
	red/green	693 580 55	plug-type
	red/yellow	693 590 55	plug-type
3 tier	red/yellow/green	693 070 55	cable
	red/yellow/green	693 570 55	plug

Available from June 2005

ACCESSORIES:

Fixing bracket, black	960 693 01
Cable gland M20 x 1.5	960 693 02
Base with integrated tube M25 x 1.5 including rubber seals, silver	960 693 06
M12 counter-plug with 5m cable	960 693 05

