

ALL DIMENSIONS IN MM / ANGLES IN DECIMAL DEGREES

DrgNo DVS-GS

TITLE DIMENSIONS FOR DVS24,48,110,240

ROXBURGH EMC

GENERAL SPECIFICATION FOR DVS

CUSTOMER
FILTER REF

Sheet 1 of 1 | Aprvd Date 19/03/01 | Aprvd By SW | Drwn by BFS | SCALE NTS | Cnn---- | Location N:\DWG\GS\GS000236

©DELTRON EMCON LTD, ROXBURGH HOUSE, FOXHILLS INDUSTRIAL PARK, SCUNTHORPE, NORTH LINCOLNSHIRE, DN15 8QJ TEL +44 1724 281770 F +44 1724 270230


PRODUCT RANGE (RATINGS @ 85°C)

| TYPE | CONTINUOUS | | TRANSIENT | |
|---------|---------------------|--------------------|-----------------------------|------------------------------|
| | RMS VOLTAGE (VOLTS) | DC VOLTAGE (VOLTS) | ENERGY (10/1000ms) (JOULES) | PEAK CURRENT (8/20ms) (AMPS) |
| DVS 24 | 30 | 38 | 8.8 | 1000 |
| DVS 48 | 60 | 81 | 20 | 4500 |
| DVS 110 | 150 | 200 | 80 | 6500 |
| DVS 240 | 275 | 369 | 140 | 6500 |

SPECIFICATION

LINE FREQUENCY DC TO 440Hz
 TEMPERATURE RANGE -25C TO +85C
 WIRE GAUGE 12 AWG
 MOUNTING EN 50 022 RAIL (TOP HAT)
 SCREW TERMINALS 2.5sqmm (12 AWG)

ELECTRICAL CONNECTION



EXAMPLE

