

Type: **M22-LEDC-G**  
 Article No.: **216562**



Ordering information			
Connection technique			Screw terminals
Description			Base fixing
Rated operational voltage	$U_e$	V	12 – 30 V AC/DC
Rated operational current	$I_e$	mA	8 – 15
Power consumption	$P_{max.}$	W	0.26 W at 24 V
Lifespan to EN 60064 at $t_a = +25\text{ °C}$	$t_{mean}$ (AC)	h	100000
Colour			Green

### Colour



### Notes concerning the product group

For pushbutton actuators, indicator lights, illuminated pushbuttons and illuminated selector switch actuators, the following applies:

M22...-R only in combination with M22-LED...-R

M22...-G only in combination with M22-LED...-G

M22...-W only in combination with M22-LED...-W

M22...-Y only in combination with M22-LED...-W

M22...-B in combination with M22-LED...-W

M22...-B or in combination with M22-LED...-B

<b>General</b>			
Standards			IEC/EN 60947 VDE 0660
Degree of protection, IEC/EN 60529			IP 20
Climatic proofing			Damp heat, constant, to IEC 60068–2–78 Damp heat, cyclic, to IEC 60068–2–30
Ambient temperature			
Open		°C	–25/70
Mounting position			As required
Mechanical shock resistance according to IEC 60068–2–27 Shock duration 11 ms, half–sinusoidal		g	> 30
Terminal capacities			
Solid		mm <sup>2</sup>	0.75 – 2.5
Stranded		mm <sup>2</sup>	0.5 – 2.5
<b>Contacts</b>			
Rated impulse withstand voltage	$U_{imp}$	V AC	6000
Rated insulation voltage	$U_i$	V	500
Overvoltage category/pollution degree			III3
<b>Notes</b>			
			> 200 V AC/60 Hz: –25/+55 °C

Moeller GmbH, Hein–Moeller–Str. 7–11, D–53115 Bonn  
E–Mail: [catalog@moeller.net](mailto:catalog@moeller.net), Internet: [www.moeller.net](http://www.moeller.net), <http://catalog.moeller.net>  
Copyright 2006 by Moeller GmbH. Subject to modifications. HPL–C2006GB–INT V2.3