


Slimline Lamp SL 025 Series with On/Off switch

Photo: Slimline lamp with on/off switch, with integrated electric socket (Germany), Art. No. 02520.0-00



- Slim casing**
- Electronic ballast**
- Lamp without/with electrical socket (choice of sockets)**
- Magnet fixing (option)**
- Energy saving lamp**
- On/Off switch**


The flat slimline lamp SL 025 is suitable for all types of panels and enclosures, especially where space is at a premium. The lamp can be mounted on its narrow or broad surface using screws. It is also available with a magnet which allows it to be fitted quickly in any position in a steel enclosure. Both versions are available with an integrated electrical socket enabling the use of additional appliances.



Technical Data

Power consumption	11W (equals 75W light bulb)
Luminosity	900Lm
Lamp type	energy saving lamp, 2G7 socket
Service life	10,000h
Switch	on/off switch for lamp
Connection	terminal 2.5mm ² with cable clamp, clamping torque 0.8Nm
Mounting	screw fixing, M5, 300mm centers magnet fixing (optional)
Casing	plastic according to UL94 V-0, light grey
Dimensions	345 x 91 x 40mm
Fitting position	narrow surface/broad surface
Operating/Storage temperature	-20 to +50°C (-4 to +122°F) / -45 to +70 °C (-49 to +158 °F)
Protection type	IP20
Note	24VDC to 48VDC on request

The slimline lamp SL 025 is also available with a 19" front panel.



Art. No.	Model	Operating Voltage	Socket	Nominal Current	Weight (approx.)	Protection class	Approvals
02520.0-00	without magnet	230VAC, 50/60Hz	Germany (1)	16.0A	0.40kg	I (earthed)	VDE
02520.1-00	with magnet	230VAC, 50/60Hz	Germany (1)	16.0A	0.60kg	I (earthed)	VDE
02521.0-00	without magnet	230VAC, 50/60Hz	France/Poland (2)	16.0A	0.40kg	I (earthed)	VDE
02521.1-00	with magnet	230VAC, 50/60Hz	France/Poland (2)	16.0A	0.60kg	I (earthed)	VDE
02522.0-00	without magnet	230VAC, 50/60Hz	Switzerland (3)	10.0A	0.40kg	I (earthed)	VDE
02522.1-00	with magnet	230VAC, 50/60Hz	Switzerland (3)	10.0A	0.60kg	I (earthed)	VDE
02523.0-00	without magnet	230VAC, 50/60Hz	UK/Ireland (4)	13.0A	0.40kg	I (earthed)	VDE
02523.1-00	with magnet	230VAC, 50/60Hz	UK/Ireland (4)	13.0A	0.60kg	I (earthed)	VDE
02524.0-01	without magnet	120VAC, 50/60Hz	USA/Canada (5)	15.0A	0.40kg	I (earthed)	UL submitted
02524.1-01	with magnet	120VAC, 50/60Hz	USA/Canada (5)	15.0A	0.60kg	I (earthed)	UL submitted
02527.0-00	without magnet	230VAC, 50/60Hz	none	-	0.40kg	II (double insulated)	VDE; UL submitted
02527.1-00	with magnet	230VAC, 50/60Hz	none	-	0.60kg	II (double insulated)	VDE; UL submitted
02527.0-10	without magnet	120VAC, 50/60Hz	none	-	0.40kg	II (double insulated)	UL submitted
02527.1-10	with magnet	120VAC, 50/60Hz	none	-	0.60kg	II (double insulated)	UL submitted