

REVISIONS				DGC, ND, SPC-F0G4 * Effective; 7/B/02 * DCP No; 1398					
DCP #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE	
1575		NOT Released	JWM	1/30/04	NF	04/01/08	JN	04/01/08	



Bulb: MR16 Base: GU5.3 Volts: 12

Watts (Amps:) 20

MOL in/mm: 1.75/44.5 MOD in/mm: 2.00/50.8

Filament: C-8

Special Desc: Faceted Reflector

Color Temperature: 3050

Average Life: 3000 Typ Use: Display 12

SPC-F004.DWG

TOLERANCES:	DRAWN BY:	DATE:	DRAW	ING TITLE:				
UNLESS OTHERWISE	Jeff McVicker	1/30/04	Dîsplay Lamp, Flood					
SPECIFIED,	CHECKED BY:	DATE:	SIZE	DWG, NO,		ELEC	TRONIC FILE	REV
DIMENSIONS ARE	Jason Nash	04/01/08	Α	E	ESX	16F676.dwg		
PURPOSES ONLY.	APPROVED BY:	DATE:					-	
	Jason Nash	04/01/08	SCALE	E: NTS	U.O.M.: INCHES [mm		SHEET: 1 (

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC
TECHNOLOGY, DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND
RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME
ALL RISK AND LIABILITY WHATSQEVER IN CONNECTION THEREMITH.