

| DCP # | REV | DESCRIPTION | DRAWN | DATE | CHECKD | DATE | APPRVD | DATE |
|-------|-----|-------------|-------|----------|--------|----------|--------|----------|
| 1858 | A | RELEASED | JWM | 04/01/08 | JN | 04/01/08 | JN | 04/01/08 |



Volts: 12
 Watts: 50
 Filament: C-8
 MOL: 1.77
 MOD: 2.0
 Avg Life: 4000 hrs
 Bulb: MR16
 Base: GU5.3
 Dichroic Reflector
 CT deg K: 3000
 Approx, Initial Max. Beam CP: 10,000
 Beam Angle: 12°
 Burning Position: Any

SPC-F004.DWG

| | | | | | | |
|--|---------------|----------|-------------------------|----------|-----------------|-----|
| TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY. | DRAWN BY: | DATE: | DRAWING TITLE: | | | |
| | Jeff McVicker | 04/01/08 | Lamp, Narrow spot MR 16 | | | |
| | CHECKED BY: | DATE: | SIZE | DWG. NO. | ELECTRONIC FILE | REV |
| | Jason Nash | 04/01/08 | A | EXT | 16F682 | A |
| APPROVED BY: | DATE: | SCALE: | U.O.M.: | SHEET: | | |
| Jason Nash | 04/01/08 | NTS | INCHES [mm] | 1 OF 1 | | |

ALL RIGHTS RESERVED. NO PORTION OF THIS PUBLICATION, WHETHER IN WHOLE OR IN PART CAN BE REPRODUCED WITHOUT THE EXPRESS WRITTEN CONSENT OF SPC TECHNOLOGY. DISCLAIMER: ALL STATEMENTS AND TECHNICAL INFORMATION CONTAINED HEREIN ARE BASED UPON INFORMATION AND/OR TESTS WE BELIEVE TO BE ACCURATE AND RELIABLE. SINCE CONDITIONS OF USE ARE BEYOND OUR CONTROL, THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR THE INTENDED USE AND ASSUME ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.