

→ Millennium power supply

- With a switch mode power supply, regulated and protected against overloads and short-circuits, these new power supply units are easily integrated in switchboards and enclosures.
- The potentiometer can be used to set the output voltage between 100 and 120% to compensate for any voltage drops on the line.
- The LED continuously signals the presence of voltage at the output and, when flashing, triggering of the self-protection.



PS 24-60 W

Part numbers

Type	Nominal output voltage	Nominal power	Code
PS	12 V ---	22 W	88950300
	24 V ---	30 W	88950301
	24 V ---	60 W	88950302

General characteristics

Environmental characteristics

Conformity to standards	EN 50081-1 EN50082-1 IEC 950
Certifications	UL-CSA, TÜV

Electrical characteristics

Input voltage	100 → 240 V ~ single-phase
Supply frequency range	50/60 Hz (+4%/-6%), or 47→ 53 Hz/ 57→ 63Hz
Output voltage (V)	Adjustable from 100 → 120%
Technology	Primary switch mode electronic power supplies
Short-circuit protection	Yes
Overload protection	Yes
Primary protection	1 A gG fuse for 88950300 and 88950301 3 A gG fuse for 88950302
Reset after overload	Automatic

Mechanical characteristics

Status indication	LED at the output
Mounting	DIN rail EN 50022

Dimensions (mm)

PS

