



## EDL Lighting limited


Redbrook Lane, Brereton, Rugeley, Staffordshire WS 15 1QU  
Tel: 01889 582112 Fax: 01889 584012 e mail: sales@edl-lighting.co.uk  
Web: www.edl-lighting.co.uk

### ***Tube Light Luminaire***

The waterproof tube light is tested to Ip67 and comes complete with brackets and a 2.75 metre trailing lead. Made from impact resistant polycarbonate tube this unit has many applications

Version: TUB-80-IP67-36W-T8-240-INT

Order Code 00690



Primary voltage:	230/240v 50/60 Hz
Lamp type:	T8 Linear Fluorescent
Wattage:	36 watt
Ballast:	High Frequency Electronic
Lamp base type	
Switch fitted Yes/No:	No
Switch location:	Not applicable
IP Rating	IP67
Base Type:	Not applicable
Fixing:	Bracket can be horizontal or vertically mounted
No of arms:	0
Length of arms	Not Applicable
Tube Material:	Impact resistant polycarbonate tube
Tube Diameter:	80mm diameter
Shield fitted:	No
End Cap Material	Moulded PVC
Brackets:	Yes
Bracket Material:	Moulded PVC
Trailing cable:	Yes 2.75m 3 core
Plug fitted	No
Manufacturing Standard:	BS EN 60598 etc
RHOS compliant	Yes
WEE Compliant	Yes
Finish & Colour:	Clear tube black end caps and brackets



# EDL Lighting limited

Redbrook Lane, Brereton, Rugeley, Staffordshire WS 15 1QU  
Tel: 01889 582112 Fax: 01889 584012 e mail: sales@edl-lighting.co.uk  
Web: www.edl-lighting.co.uk

The waterproof tube light is tested to IP 67 and comes complete with brackets and a 2.75 metre trailing lead. Made from impact resistant polycarbonate tube this unit has many applications

Version: TUB-80-IP67-36W-T8-240-INT

Order Code 00690

## Features

- Impact resistant polycarbonate tube
- High IP Rating IP67
- Linear fluorescent tube
- Clamps and ballasts are supplied
- Suitable for machine mounting - withstands coolant spray onto light
- Other marine and waterproof applications
- Design allows for ease of cleaning
- Can be used in dusty environments
- Trailing lead fitted
- Clip on bracket securing straps

