

600 mm LED Light Bar (White SMD multi-LED)	LB6002012CW
---	--------------------

606
Max

11 16

r8

Mounting Clips

Typical light distribution at overhead distance 50 cm

Lux (Lm/m²)

75
50
25
0 cm
-25
-50
-75

75
50
25
0 cm
-25
-50
-75

350 l
250 l
150 l
100 l

a
a
b
b'

All dimensions in mm

Product Characteristics

Operating Voltage	24VDC
Power Consumption	12W
Number of LED rows	Two
Number of LEDs	120
Overall Length	606 mm Maximum.
Nominal Light output	440 Lumens
Colour Temperature	5500°K (Cool White)
Viewing Angle	100°
Power Connector	ø3.5mm x 1.3mm
Life Duration	20,000 hours.
Ingress Protection Rating	IP40
Construction	Rigid circuit board (2-off) within matt aluminium casing, clear acrylic lens cover and end caps.

Notes.

- 1) Light Bar supplied with two mounting clips and one daisy-chain connector.
- 2) RoHS compliant.

600 mm LED Light Bar (White SMD multi-LED)	LB6002012NW
---	--------------------

606 Max

11 16

r8

Mounting Clips

Typical light distribution at overhead distance 50 cm

Lux (Lm/m²)

75 50 25 0 cm -25 -50 -75

-75 -50 -25 0 cm 25 50 75

100 l 150 l 250 l 350 l

a a' b b'

All dimensions in mm

Product Characteristics

Operating Voltage	24VDC
Power Consumption	12W
Number of LED rows	Two
Number of LEDs	120
Overall Length	606 mm Maximum.
Nominal Light output	400 Lumens
Colour Temperature	3500°K (Neutral White)
Viewing Angle	100°
Power Connector	ø3.5mm x 1.3mm
Life Duration	20,000 hours.
Ingress Protection Rating	IP40
Construction	Rigid circuit board (2-off) within matt aluminium casing, clear acrylic lens cover and end caps.

Notes.

- 1) Light Bar supplied with two mounting clips and one daisy-chain connector.
- 2) RoHS compliant.