



SMD Super Bright LED


OVS-30 Series

Features:

- Standard PLCC-4 Package
- High Reliability LED Package
- Super Wide Viewing Angle







Maximum Ratings at Ta=25℃

Reverse Voltage (<100 μA)	5.0V
D.C. Forward Current	
Pulse Current (Pulse Width of 0.1ms, 1/10 Duty Cycle)	100mA
Operating Temperature Range	25 to +85°C
Storage Temperature Range	40 to +100°C
Soldering Temperature Dip Soldering	260°C for 5 secs
Soldering Temperature Hand Soldering	350°C for 3 secs

Electrical & Optical Characteristics at Ta=25°C

	LED Chip			Dominant Wavelength	Luminous Intensity (mcd) at 20mA		Forward Voltage (V) at 20mA		Viewing Angle	
Ant Part No.	Material	Emitted Colour	Brightness	Lens Colour	(nm) at 20mA	min.	typ.	typ.	max.	2 0 1/2 (deg)
OVS-3003	InGaN / Sapphire	Blue	Mega	Water Clear	465	80	200	3.2	4.0	120
OVS-3004	InGaN / Sapphire	True Green	Mega	Water Clear	520	270	500	3.2	4.0	120
OVS-3006	A1GaInP/Si	Yellow	Mega	Water Clear	589	200	450	2.1	2.5	120
OVS-3008	A1GaInP/Si	Red	Mega	Water Clear	625	200	420	2.1	2.6	120

	LED Chip				Co-Ordinates for CIE Chromaticity		Luminous Intensity (mcd) at 20mA		Forward Voltage (V) at 20mA		Viewing Angle
Ant Part No.	Material	Emitted Colour	Brightness	Lens Colour	at 20mA X Axis	Y Axis	min.	typ.	typ.	max.	2 0 1/2 (deg)
OVS-3001	InGaN/Sapphire	White	Mega	Water Clear	0.31	0.30	500	1250	3.2	4.0	120

Disclaimer This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was a ware of the possibility of such loss or damage a rising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. SPC Multicomp is the registered trademark of the Group. © Premier Farnell plc 2008.

http://www.farnell.com http://www.newark.com http://www.cpc.co.uk

